

Shaw 4000 Specification

SHAW 4000 CARPET SEAM SEALER

Any variance from these procedures will become the responsibility of the installer and not the manufacturer. For specific questions regarding Shaw 4000 not covered within this document contact Shaw Contract Group at 1.877.502.7429 or at www.shawcontractgroup.com.

Shaw requires the use of seam sealer on all carpet products with the exception of carpet tile products. Shaw 4000 is a non-flammable seam sealer recommended for sealing cut edges of carpet to prevent raveling.

FEATURES AND BENEFITS

- Applies easily with applicator tip
- CRI Green Label Plus certified and SCAQMD Compliant

Case Qty./Weight	Pallet Qty.	Pallet Case Weight
12 qts./22 lbs.	45 Cases	1040 lbs.

Laboratory Tests	Results
Polymer type	Latex Polymer
Percent solids	55-57%
VOCs Rule #1168 of California's SCAQMD	6 g/L
Roll-ability	Easy
Density	8-9 lbs.
Consistency	Paste
Color	White, dries clear
Tracer	UV Fluorescent
Shelf life	1 year when stored in original packaging at 73° F (23°C)
Storage conditions	65°F to 95°F (18°C to 35°C)
Flash point (ASTM D56)	NA
Protect from traffic	30 minutes

Protect containers from freezing in transit and storage. Provide for heated storage on site and deliver all materials at least 24 hours before work begins.

LEED (VERSION 3.0) CONTRIBUTION

MR Credit 5, Regional Materials	Up to 2 points
IEQ Credit 4.1, Low-emitting Materials, Adhesives & Sealants	1 point
IEQ Credit 4.3, Low-emitting Materials, Flooring Systems	1 point

ENVIRONMENTAL INFORMATION

- CRI Green Label Plus Certified #59126
- Meets requirements of California South Coast Air Quality Management District Rule 1168
- Meets requirements of California Department of Public Health Section 01350

1-YEAR WARRANTY

This product is covered by a 1-year limited warranty. For information on this limited warranty, please ask your authorized Shaw retailer or contact Shaw contract Group at 1.877.502.7429.

APPROXIMATE PRODUCT COVERAGES

Application	Coverage
1/8" bead	550-600 linear feet

Coverages shown are for estimating purposes only. Actual jobsite coverages may vary according to applicator tip size and application.

APPLICATION

- Prepare carpet according to Shaw's Installation Guidelines.
- Apply a bead of seam sealer along the carpet primary backing using the applicator tip provided with the bottle.
- When direct gluing carpet apply seam sealer to only one side of the carpet. When stretching in carpet apply seam sealer to both sides of the carpet.
- Complete the seam by butting both sections of the carpet together while the seam sealer is still wet (within 5-10 minutes). When stretching in carpet, allow both seam sealed edges to dry to a clear state before hot melting the seam.

CLEAN-UP

To remove smears of seam sealer from the carpet surface within 10 minutes use a clean cloth wet with soapy water. Do not apply soapy water directly on carpet. Clean with mineral spirits once dried. Use caution with mineral spirits, which may be harmful to some materials.

102013