

Wall Base Adhesive

141VS Tube Wall Base Adhesive (Twelve 30/oz tubes per carton, sold by carton only)

166VS Wall Base Adhesive (1 Gallon)

- Solvent Free
- Rubber & Vinyl Wall Base
- Exceptional Wet Grab
- Low Odor

Instructions

Shaw Contract Group Wall Base Adhesive is a premium light-colored, solvent-free acrylic adhesive for installing wall base on clean, dry interior walls. It has the powerful wet strength needed to hold Wall Base firmly to the wall until it dries.

ADVANTAGES:

- Good grab
- SCAQMD Rule 1168 – compliant
- Low odor
- Easy Clean Up
- Freeze thaw protection to 15 degrees F

APPLICATION:

- 1.) Spread the adhesive using the appropriate trowel or using a tube applicator tip.
- 2.) The adhesive may be spread on the wall surface or on the back of the wall base.
- 3.) Immediately place the wall base into position while the adhesive is freshly applied.
- 4.) Roll the entire strip of base with a small roller in the direction of the previously placed strip.
- 5.) Wipe smudges and clean spills quickly before the adhesive dries. Use a clean cloth dampened with water. Clean tools with water while the adhesive is still wet.
- 6.) Dried adhesive may require the use of a solvent (odorless mineral spirits).

CAUTION:

Make certain the surface is porous by cutting away or perforating non-absorbent wall coverings. Do not apply to vinyl wallpaper. We cannot be responsible for shrinkage caused by unstable Wall Base.

Coverage on 4" cove (10.16 cm cove):

1/8" x 1/8" V-Notch = 220-240 linear feet per gallon

3 Hole Applicator Tip = 55-60 linear feet per carton

Coverage on 4" Wall Base (10.16 cm): 1/8" x 1/8" V-Notch = 220 -240 linear feet per gallon.

OPEN TIME:

20 – 30 Minutes

SHELF LIFE:

Two years from manufacturing date in an unopened container.

Avoid excessive heat or cold. Protect from freezing – store at temperatures between 65 degrees and 95 degrees F.

WALL SURFACES:

Plaster, brick, wood, concrete, gypsum, drywall, plywood.

VOC content is below and is established by California SCAQMD Rule 1168.

PRODUCT IDENTIFIER:

Shaw Contract Group Wall Base Adhesive/Shaw

Cove Base Adhesive 24-Hour Emergency in the USA: Chemtrec 800.424.9300

PRECAUTIONARY STATEMENTS:

In case of eye contact, flush with water for 10 -15 minutes. If irritation persists contact a physician. If prolonged skin contact causes irritation, wash with soap and water. If swallowed, consult a physician.

Safety glasses and gloves are recommended if contact is expected.

Dispose of in accordance with local, regional, national, international regulations as

specified. DOT Hazard Class: Unregulated.

Read SDS for detailed product information.

SDS is available by calling Inforum at 877.502.7429

LEED PROGRAM CERTIFICATIONS: (where applicable)

IEQ Credit 4.1 – Low emitting materials

IEQ Credit 4.3 – Low VOC ratings help qualify installations for this credit as part of a flooring system

MR Credit 5 – Regional Materials – on jobsites within 500 miles of manufacturing location: Dalton, GA 30721