

## SHAW 4151

---

### DESCRIPTION:

Shaw 4151 is an enhanced formulated universal performance adhesive designed for multiple backing systems, including resilient (sheet/lvt/lvp), carpet tile and non-patterned EPBL.

### APPROVED SUBSTRATES:

- For interior use only.
- Wood Association approved wood underlayment and subflooring. See Resilient Wood Substrate Information.
- Gypsum and lightweight concrete (primed with Shaw 9050).
- Sound and properly prepared concrete (on, above or below grade), metal, wood fiberglass and terrazzo.
- Existing resilient products should be over 1 year old, secure and fully adhered with a full spread of adhesive. Remove all waxes and polishes from the existing floor before installation.

### SUBSTRATE TESTING:

- RH - 99% (ASTM F-2170), provided the site is absent of hydrostatic pressure.
- CaCl / MVER - 12 lbs (ASTM F-1869)
- pH 12 (ASTM F-710)
- For on-grade / below grade installations, CaCl, RH and pH testing are required.
- For above grade installations, RH testing is required.

For older slabs or slabs with a prior history of moisture related issues, Shaw Technical Support recommends moisture mitigation in the form of a 2-part epoxy system, such as MoistureTEK. For newer slabs with an intact moisture retarder, initial moisture levels should recede over time.

### SUBSTRATE PREPARATION:

- Substrate must be structurally sound, clean, level and dry.
- Substrate must be free of dust, dirt, oil, grease, paint, curing agents, concrete sealers, adhesives, loosely bonded toppings, loose particles and any other substance or condition that may prevent or reduce adhesion.
- Do not use over substrates containing asbestos or active cutback adhesive.
- Fill depressions or cracks with a cementitious patching / leveling compound that meet or exceed Shaw Industries maximum moisture level and pH requirements. Use of gypsum-based patching and/or leveling compounds which contain Portland or high alumina cement and meet or exceed the compressive strength of 3,000 psi are acceptable.
- For cracks and saw cuts deeper than 1", Shaw QuickFil is recommended.
- Installation site must be acclimated with HVAC in operation, or the temperature must be controlled between 65-95° F (18- 35°C) and the ambient relative humidity controlled between 30-65% before, during and permanently after the installation.
- Do not use over chemically abated substrates.

### APPLICATION INSTRUCTIONS AND SPREAD RATES:

- Spread adhesive using the recommended trowel.

# Specification

Read and follow the product specific installation guidelines for layout, design and any special instructions for installation.

- Spread adhesive evenly over substrate, keeping the trowel at a 45° angle to the substrate.
- After each flooring type installation, roll with a 75-100 lb roller.

## For non-porous substrates:

Flooring Type	Trowel Size	Coverage
LVT/LVP	1/16" x 1/32" x 1/32" U notch	19-22 yds <sup>2</sup> /gallon (175-225 ft <sup>2</sup> /gal)
Vinyl Sheet	1/16" x 1/32" x 1/32" U notch 3/8" Nap Roller	19-22 yds <sup>2</sup> /gallon (175-225 ft <sup>2</sup> /gal) 35-40 yd <sup>2</sup> /gallon (300-350 ft <sup>2</sup> /gal)

## For porous substrates:

Flooring Type	Trowel Size	Coverage
LVT/LVP	1/16" x 1/16" x 1/16" Sq notch	15-19 yd <sup>2</sup> /gallon (140-170 ft <sup>2</sup> /gal)
Vinyl Sheet	1/16" x 1/16" x 1/16" Sq notch 3/8" Nap Roller	15-19 yd <sup>2</sup> /gallon (140-170 ft <sup>2</sup> /gal) 35-40 yd <sup>2</sup> /gallon (300-350 ft <sup>2</sup> /gal)

**Note:** For LVT/LVP/Sheet Vinyl: install into semi-wet adhesive.

**Note:** For vinyl, back roll the adhesive with a short nap roller to reduce telegraphing of adhesive ridges.

## For Semi-Wet set installations:

Flash Time	10-20 minutes
Working Time	20-30 minutes*
Cure Time	24 Hours

Flooring Type	Trowel Size	Coverage
Carpet Tile	1/16" x 1/32" x 5/64" U notch 3/8" Nap Roller	28-33 yd <sup>2</sup> /gallon (250-300 ft <sup>2</sup> /gal) 35-40 yd <sup>2</sup> /gallon (300-350 ft <sup>2</sup> /gal)
Reworx	1/16" x 1/32" x 1/32" U-notch	19-22 yd <sup>2</sup> /gallon (175-225 ft <sup>2</sup> /gal)
CushionWorx	3/8" nap roller	35-40 yds <sup>2</sup> /gallon (300-350 ft <sup>2</sup> /gal)
DuraWorx	Carpet Tile to Cushion 3/8" nap roller  Cushion to Subfloor 1/16" x 1/16" x 1/16" U or Square notch	35-40 yds <sup>2</sup> /gallon (300-350 ft <sup>2</sup> /gal)   18-20 yds <sup>2</sup> /gallon (160-180 ft <sup>2</sup> /gal)

**Note:** Install as a pressure sensitive adhesive.

# Specification

Flooring Type	Trowel Size	Coverage
EPBL non-patterned carpet	3/32" x 3/32" x 3/32" U-notch	8-9 yds <sup>2</sup> /gallon

**Note:** Carpet must be laid into wet adhesive.

**Note:** Coverage rate, flash time and working time may vary based on temperature, humidity, substrate porosity, jobsite conditions and application practices. Coverages are estimates only. Actual jobsite coverage may vary according to substrate conditions, type of trowel used and setting practices. Trowel dimensions are width/depth/space.

**\*Areas with low relative humidity will result in reduced working time.**

## PRODUCT CHARACTERISTICS:

Read and follow the product specific installation guidelines for layout, design and any special instructions for installation.

Weight	34 lbs / 4 gallon pail
Pallet Quantity	36
Pallet Weight	1480 lbs
Polymer Type	Acrylic
Percent Solids	40-60%
VOC's (Rule #1168 of California SCAQMD)	<0.5 g/L
Color / Tracer	Off-white / with fluorescent blue
Shelf Life	2 years from manufacturing date, in an unopened container
Storage Conditions	65°F to 95°F (18°C to 35°C). Protect from freezing
Flash point (ASTM D56)	>212°F / 100°C
Cleaning Instructions	Use warm soapy water while adhesive is still wet. For dried adhesive removal contact Shaw Technical Support at 1-800-471-7429
Traffic	Light Traffic - 12 hours Heavy Traffic - 24 hours
Heat Welding	Minimum 12 hours after installation

## ENVIRONMENTAL

- California South Coast Air Quality Management District Rule 1168
- California Department of Public Health Section 01350
- Greenguard / Greenguard Gold - #216283-410/216283-420

## LEED IEQ CREDIT INFORMATION (2009 AND V4)

Credit Requirement	Status	Comment
--------------------	--------	---------

# Specification



Meets General Emissions Evaluation Criteria	Complies	Greenguard / Greenguard Gold 216283-410/216283-420
VOC's (Rule #1168 of California SCAQMD amended October 6, 2017)	Complies	VOC Content < 50 g/L

## WARRANTY:

This product is covered by a 10 year limited warranty and under bed warranty when used with specific products. For more detailed information on this limited warranty, please see contact information at the bottom of this page.