

## Shaw 4062 For Fiberglass Sheet Goods – Seam Sealer

Shaw 4062 Premium Seam Sealer is a solvent-free sealer designed for seaming fiberglass sheet goods in direct glue down installations.

### DIRECTIONS:

1. Prepare flooring and seam according to flooring manufacturer's instructions.
2. Apply a bead of 4062 Seam Sealer to the foamed edges of the fiberglass sheets to be seamed.
3. Join the sheet edges by butting them together while the seam sealer is still wet.
4. Wipe off any excess seam sealer with a clean damp cloth.
5. Dried sealer can be removed with Shaw adhesive remover. Avoid soaking the flooring with solvent. Do not pour solvent directly onto flooring.
6. Protect the seam area for a minimum of 6 hours to allow the seam sealer to dry. The adhesive, floor covering, and area to receive resilient flooring must be maintained at a temperature of 65°-95°F (18°-35°C) and at a relative humidity of 30-60% for 72 hours before, during, and after installation.

### PHYSICAL PROPERTIES

V.O.C.	Negligible
Base	Acrylic polymer blend
Color	Off white
Consistency	Liquid
Open Time	Up to 1 hour depending on the porosity of the subfloor.
Shelf Life	One year in unopened container at 70°F
Coverage	225 linear feet per 8oz
Flammability	Non-flammable. Complies with NFPA Class A and UBC Class 1 as determined by ASTM E84 and also passes the Pill Test.
Other features	Waterproof when cured, VOC compliant, freeze/ thaw stable to 10°F (-12.22°C). While this adhesive is freeze-thaw stable, it is still necessary to protect from freezing.
Clean Up	Use soap and water while wet. Use Shaw adhesive remover when dry.

**CAUTION: DO NOT** take internally. If swallowed, **DO NOT** induce vomiting. Call a physician immediately. **KEEP OUT OF REACH OF CHILDREN.**

**WARRANTY INFORMATION:** This product is manufactured according to exacting quality control standards and is warranted to be free from manufacturing defects. Defective material called to our attention within one year of manufacture will be replaced. No guarantee, expressed or implied, is made regarding the performance

of this product since the manner and conditions of application are beyond our control. *For complete warranty information, call SHAW Tech Services at 1.800.257.7429. You may also visit us on the web at: [shawcontract.com](http://shawcontract.com)*