

Loch

Collection	Unite	
Style Number	1028V	
Aspect	Heavy Commercial Luxury Vinyl Tile With Fiberglass	
class	Class III, Type B	
Finish	ExoGuard®	
	Metric	U.s.
Nominal Dimensions	25 cm w x 100 cm l	10 in w x 39 in l
Actual Dimensions	25.00 cm w x 100.00 cm l	9.84 in w x 39.37 in l
Wear Layer Thickness	0.56 mm	22 mil (0.022 in)
Overall Product Thickness	5 mm	0.197 in
Edge Profile	Squared Edge	
Installation Type	Loose Lay	
Recommended Adhesive	2200 Resilient Tile 4 Gallon	

Packaging

Pieces Per Box	10 pcs	
Area Per Box	2.5 sq m	26.91 sq ft
Weight Per Box	14.44 kg	31.83 lbs



Recommended Installation Method



Coordinating Products

LVT: Inlet, Cove

Warranties

15 Year Commercial Limited

Product Transparency

Shaw Contract is dedicated to providing clients with a building chemistry that's safe and dependable. Working together, we will help you meet your goals as they pertain to material health. Luxury Vinyl Tile products are UL Certified with an Industry-Wide EPD and are assessed for impacts on human health and the environment.

Material Health & Environmental Certifications

Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore®	Certified
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Country of Origin	South Korea

WELL V2 Contribution Credit







X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization	FloorScore Certificate

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore Certified

Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. Visit shawcontract.com/testing for more information.	
Maintenance Guidelines		

Light Reflectance Value

					
Granite 15111 LRV 28.7	Cashmere 15114 LRV 40.7	Boulder 15506 LRV 17	Cement 15518 LRV 24.1	Gravel 15530 LRV 23.1	Sediment 15595 LRV 11.7