

Native Origins

スタイルナンバー	0116V	
建設	軽量タイプの商業用高級ビニルタイル	
クラス	Class III, Type B	
仕上げ	ExoGuard®	
	米国	メートル法
公称寸法	6 in w x 48 in l	15 cm w x 122 cm l
実際の寸法	6.00 in w x 48.00 in l	15.24 cm w x 121.92 cm l
摩耗層の厚さ	12 mil (0.012 in)	0.3 mm
製品全体の厚さ	0.098 in	2.5 mm
エッジプロファイル	スクエア エッジ	
Installation Type	Dry Back	
インストール	Direct Glue	
推奨接着剤	S150-95 Resilient Tile Spray, , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

包装

ボックスあたりの個数	18 pcs	
ボックスあたりの面積	35.95 sq ft	3.34 sq m
ボックスあたりの重量	30.42 lbs	13.8 kg



推奨インストール方法



パフォーマンス + テスト

静荷重 (astm F970)	Passes (Modified), *1500 lbs	このテストは、さまざまなスタイルと構造の相対的な特性を比較することを目的としています。結果は実験室でのテストに基づいており、比較の目的で使用されています。実際の負荷制限は異なる場合があります。
残留圧痕 (astm F1914)	Passes	
耐熱性 (astm F1514)	Passes	
耐光性 (astm F1515)	Passes	
耐薬品性 (astm F925)	Passes	
放射パネル (astm E648)	Passes, Class I	
摩擦係数(astm D2407、滑り抵抗)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

7年間の商用限定保証

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

属性+認定

Health & Wellbeing	
Indoor Air Quality	FloorScore® 認証取得
Climate Impact	
Environmental Product Declaration (EPD)	ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得
Embodied Carbon (Cradle to Gate)	7.31 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) 第三者認証取得 Country of Origin Imported

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築 環境製品宣言-オプション1：環境製品宣言（EPD） EQクレジット：低排出材料 オプション1：製品カテゴリの計算	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 FloorScore Certified
Installation Guidelines Maintenance Guidelines	Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs. Visit shawcontract.com/testing for more information.

Available Colorways



Bleached Oak 00140
V2 - Slight Variation



Northern Maple 00200
V2 - Slight Variation



Light Oak 00240
V2 - Slight Variation



Golden Oak 00260
V2 - Slight Variation



Natural Teak 00280
V2 - Slight Variation



Rose Wood 00650
V2 - Slight Variation



Bay Chestnut 00710
V3 - Moderate Variation



Hand Hewn Figur 00722
V2 - Slight Variation



Barnwood 00740
V2 - Slight Variation



Black Forest 00780
V3 - Moderate Variation



Cherry Wood 00840
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation