

Quiet Cover


Style Number	0186V	
Construction	Heavy Comm Luxury Vinyl Tile W/ In*step Backing	
Class / ASTM F1700	Class III, Type B	
Finish	ExoGuard®	
	U.s.	Metric
Nominal Dimensions	7 in w x 48 in l	18 cm w x 121 cm l
Actual Dimensions	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.197 in	5 mm
Edge Profile	Micro-Bevel	
Installation Type	Click	
Installation	Floating	

Packaging

Pieces Per Carton	8 pcs	
Area Per Carton	19.27 sq ft	1.79 sq m
Weight Per Carton	33.7 lbs	15.29 kg



Recommended Installation Method



Performance + Testing

Residual Indentation (Astm F1914)	Passes
Resistance To Heat (Astm F1514)	Passes
Resistance To Light (Astm F1515)	Passes
Resistance To Chemicals (Astm F925)	Passes
Radiant Panel (Astm E648)	Passes, Class I
Coefficient Of Friction (Astm D2407, Slip Resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited

Material Health & Environmental Certifications

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certified

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)
Total Recycled Content

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
7.31 Kg Co₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | Imported

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization
Material Ingredients - Option 1: Material Ingredient Reporting

Health Product Declaration (HPD) | 100 Ppm Disclosure

MR Credit: Building Product Disclosure and Optimization
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore Certified

EQ Credit: Low Emitting Materials
Option 1: Product Category Calculations

[Installation Guidelines](#)
[Maintenance](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways



Cottonwood 00120
V2 - Slight Variation



Canadian Maple 00200
V1 - Uniform Appearance



Wheat 00220
V2 - Slight Variation



Red Oak 00240
V2 - Slight Variation



Urban Ash 00540
V2 - Slight Variation



Cherokee 00700
V2 - Slight Variation



Mink 00720
V2 - Slight Variation



Timber 00750
V2 - Slight Variation



Lodge 00760
V2 - Slight Variation



Reclaimed 00770
V3 - Moderate Variation



Black Walnut 00790
V2 - Slight Variation





American Cherry 00820
V2 - Slight Variation





 **Quick Ship** Immediately (In Stock Australia)

Color and Visual Variation Index
Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1

Uniform Appearance

V2

Slight Variation

V3

Moderate Variation

V4

Substantial Variation

