

## Quiet Cover


Número Do Produto	<b>0186V</b>	
Construção	<b>Vinílico Lvt De Uso Comercial, Tráfego Pesado, Com Base In*step</b>	
classe	<b>Class III, Type B</b>	
Acabamento	<b>ExoGuard®</b>	
	U.s.	Metric
Dimensões Nominais	<b>7 in w x 48 in l</b>	<b>18 cm w x 121 cm l</b>
Dimensões Reais	<b>7.28 in w x 47.72 in l</b>	<b>18.49 cm w x 121.21 cm l</b>
Espessura Da Camada De Uso	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Espessura Total Do Produto	<b>0.197 in</b>	<b>5 mm</b>
Perfil De Borda	<b>Micro-Chanfrado</b>	
Installation Type	<b>Click</b>	
Instalação	<b>Floating</b>	

## Empacotamento

Peças Por Caixa	<b>8 pcs</b>	
Área Por Caixa	<b>19.27 sq ft</b>	<b>1.79 sq m</b>
Peso Por Caixa	<b>33.7 lbs</b>	<b>15.29 kg</b>



## Método De Instalação Recomendado



## desempenho + teste

recuo residual (ASTM F1914)	<b>Passes</b>
resistência ao calor (ASTM F1514)	<b>Passes</b>
resistência à luz (ASTM F1515)	<b>Passes</b>
resistência a produtos químicos (ASTM F925)	<b>Passes</b>
painel radiante (ASTM E648)	<b>Passes, Class I</b>
coeficiente de atrito (ASTM D2407, resistência ao deslizamento)	<b>≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Garantias

[15 Anos Comercial Limitada](#)

Atributos + Certificações

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	7.31 Kg Co <sub>2</sub> /M <sup>2</sup>
Life-Cycle Carbon Emissions	Low Embodied Carbon
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>FloorScore Certificate</b>

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção Ingredientes materiais - Opção 1: Relatório de ingredientes materiais	<b>Health Product Declaration (HPD)   100 Ppm Disclosure</b>
MR Credit: Divulgação e otimização de produtos de construção Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
Crédito de EQ: Materiais de baixa emissão Opção 1: cálculos de categoria de produto	<b>FloorScore® Certified</b>

Installation Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

 Cottonwood 00120 V2 - Slight Variation	 Canadian Maple 00200 V1 - Uniform Appearance	 Wheat 00220 V2 - Slight Variation	 Red Oak 00240 V2 - Slight Variation	 Urban Ash 00540 V2 - Slight Variation	 Cherokee 00700 V2 - Slight Variation
 Mink 00720 V2 - Slight Variation	 Timber 00750 V2 - Slight Variation	 Lodge 00760 V2 - Slight Variation	 Reclaimed 00770 V3 - Moderate Variation	 Black Walnut 00790 V2 - Slight Variation	 American Cherry 00820 V2 - Slight Variation
 Toffee 00830 V1 - Uniform Appearance	 Redwood 00840 V3 - Moderate Variation				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

