

Quiet Cover


Numéro De Style	0186V	
Construction	Carreau De Vinyle De Luxe Heavy Comm Avec Support In*step	
classe	Class III, Type B	
Finition	ExoGuard®	
	Impérial	Métrique
Dimensions Nominales	7 in w x 48 in l	18 cm w x 121 cm l
Dimensions Réelles	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Épaisseur De La Couche d'Usure	20 mil (0.02 in)	0.51 mm
Épaisseur Générale Du Produit	0.197 in	5 mm
Profil Du Bord	Micro-Biseau	
Installation Type	Click	
Installation	Floating	

Emballage

Pièces Par Carton	8 pcs	
Surface Par Carton	19.27 sq ft	1.79 sq m
Poids Par Carton	33.7 lbs	15.29 kg



Méthodes d'Installation Conseillées



Performance + Tests Et Essai

Poinçonnement Rémanent (Astm F1914)	Passes
Résistance À La Chaleur (Astm F1514)	Passes
Résistance À La Lumière (Astm F1515)	Passes
Résistance Chimique (Astm F925)	Passes
Coefficient De Frottement (Astm D2407, Résistance Au Glissement)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)

Attributs + Certifications

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017

Embodied Carbon (Cradle to Gate)

7.31 Kg Co₂/M²

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Agréé

Country of Origin | Imported

Contribution Au Certificat Vert Leed

« Crédit MR : Divulgarion et optimisation des produits de construction

« Crédit MR : Divulgarion et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions

Installation Guidelines

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Cottonwood 00120 V2 - Slight Variation	Canadian Maple 00200 V1 - Uniform Appearance	Wheat 00220 V2 - Slight Variation	Red Oak 00240 V2 - Slight Variation	Urban Ash 00540 V2 - Slight Variation	Cherokee 00700 V2 - Slight Variation
					
Mink 00720 V2 - Slight Variation	Timber 00750 V2 - Slight Variation	Lodge 00760 V2 - Slight Variation	Reclaimed 00770 V3 - Moderate Variation	Black Walnut 00790 V2 - Slight Variation	American Cherry 00820 V2 - Slight Variation



Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

