

Quiet Cover


Número Do Produto	0186V	
Construção	Vinílico Lvt De Uso Comercial, Tráfego Pesado, Com Base In*step	
classe	Class III, Type B	
Acabamento	ExoGuard®	
	U.s.	Metric
Dimensões Nominais	7 in w x 48 in l	18 cm w x 121 cm l
Dimensões Reais	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Espessura Da Camada De Uso	20 mil (0.02 in)	0.51 mm
Espessura Total Do Produto	0.197 in	5 mm
Perfil De Borda	Micro-Chanfrado	
Installation Type	Click	
Instalação	Floating	

Empacotamento

Peças Por Caixa	8 pcs	
Área Por Caixa	19.27 sq ft	1.79 sq m
Peso Por Caixa	33.7 lbs	15.29 kg



Método De Instalação Recomendado



Desempenho + Teste

Recuo Residual (Astm F1914)	Passes
Resistência Ao Calor (Astm F1514)	Passes
Resistência À Luz (Astm F1515)	Passes
Resistência A Produtos Químicos (Astm F925)	Passes
Coeficiente De Atrito (Astm D2407, Resistência Ao Deslizamento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

15 Anos Comercial Limitada

Atributos + Certificações

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	7.31 Kg Co <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	FloorScore®   Certificado
	Country of Origin   Imported

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção Ingredientes materiais - Opção 1: Relatório de ingredientes materiais	Health Product Declaration (HPD)   100 Ppm Disclosure
MR Credit: Divulgação e otimização de produtos de construção Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito de EQ: Materiais de baixa emissão Opção 1: cálculos de categoria de produto	FloorScore Certified
Installation Guidelines	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information.

Available Colorways

					
Cottonwood 00120 V2 - Slight Variation	Canadian Maple 00200 V1 - Uniform Appearance	Wheat 00220 V2 - Slight Variation	Red Oak 00240 V2 - Slight Variation	Urban Ash 00540 V2 - Slight Variation	Cherokee 00700 V2 - Slight Variation
					
Mink 00720 V2 - Slight Variation	Timber 00750 V2 - Slight Variation	Lodge 00760 V2 - Slight Variation	Reclaimed 00770 V3 - Moderate Variation	Black Walnut 00790 V2 - Slight Variation	American Cherry 00820 V2 - Slight Variation



**Color and Visual Variation Index**

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

