

Uncommon Ground 4"

Collection	Uncommon Ground	
Numéro De Style	0187V	
Construction	Carreau De Vinyle De Luxe Commercial Lourd	
classe	Class III, Type B	
Finition	ExoGuard®	
	Impérial	Métrique
Dimensions Nominales	4 in w x 36 in l	10 cm w x 92 cm l
Dimensions Réelles	3.94 in w x 36.22 in l	10.01 cm w x 92.00 cm l
Épaisseur De La Couche d'Usure	20 mil (0.02 in)	0.51 mm
Épaisseur Générale Du Produit	0.118 in	3 mm
Profil Du Bord	Bord Carré	
Installation Type	Dry Back	
Installation	Direct Glue	
Adhésif Recommandé	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon	



Emballage

Pièces Par Carton	36 pcs	
Surface Par Carton	35.65 sq ft	3.31 sq m
Poids Par Carton	41.5 lbs	18.82 kg

Méthodes d'Installation Conseillées



Coordination Des Produits

LVT: Uncommon Ground 6"

Performance + Tests Et Essai

Poinçonnement Rémanent (Astm F1914)	Passes
Résistance À La Chaleur (Astm F1514)	Passes
Résistance À La Lumière (Astm F1515)	Passes
Résistance Chimique (Astm F925)	Passes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)  
[Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient](#)

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Attributs + Certifications

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | Divulcation De 100 ppm

Climate Impact

Environmental Product Declaration (EPD)

Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017

Embodied Carbon (Cradle to Gate)

6.05 Kg Co<sub>2</sub>/M<sup>2</sup>

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Agréé  
CE Marking (EN 14041) | Certifié Par Un Tiers  
Country of Origin | Imported

Contribution Au Certificat Vert Leed

- « Crédit MR : Divulcation et optimisation des produits de construction
- « Crédit MR : Divulcation et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)  
[Maintenance Guidelines](#)

























**Health Product Declaration (HPD) | 100 Ppm Disclosure**  
**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**  
**FloorScore Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.




Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

## Available Colorways

					
Provence 02140 V2 - Slight Variation	Driftwood 02150 V2 - Slight Variation	Sand Dune 02160 V2 - Slight Variation	Gallery Maple 02200 V2 - Slight Variation	French Grey 02500 V3 - Moderate Variation	White Oak 02506 V2 - Slight Variation
					
Zen 02520 V1 - Uniform Appearance	Teak Light 02530 V3 - Moderate Variation	Brazilian Chry 02534 V3 - Moderate Variation	Telluride 02540 V4 - Substantial Variation	Teak Green 02544 V2 - Slight Variation	Skyline 02560 V2 - Slight Variation
					
Cikel Cherry 02571 V2 - Slight Variation	Asian Mahogany 02572 V2 - Slight Variation	Chocolate Chry 02573 V2 - Slight Variation	Whiskey Barrel 02580 V2 - Slight Variation	Olivewood 02700 V3 - Moderate Variation	Bamboo Natural 02701 V2 - Slight Variation
					
Bamboo Coffee 02702 V2 - Slight Variation	Heritage 02710 V2 - Slight Variation	Adirondack 02720 V2 - Slight Variation	Gallery Walnut 02740 V3 - Moderate Variation	Colonial 02750 V2 - Slight Variation	Ceylon 02760 V2 - Slight Variation

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1	V2	V3	V4
			
Uniform Appearance	Slight Variation	Moderate Variation	Substantial Variation

