

Uncommon Ground 6"

Collection	Uncommon Ground	
Numéro De Style	0188V	
Construction	Carreau De Vinyle De Luxe Commercial Lourd	
classe	Class III, Type B	
Finition	ExoGuard®	
	Impérial	Métrique
Dimensions Nominales	6 in w x 36 in l	15 cm w x 92 cm l
Dimensions Réelles	5.91 in w x 36.22 in l	15.01 cm w x 92.00 cm l
Épaisseur De La Couche d'Usure	20 mil (0.02 in)	0.51 mm
Épaisseur Générale Du Produit	0.118 in	3 mm
Profil Du Bord	Bord Carré	
Installation Type	Dry Back	
Installation	Direct Glue	
Adhésif Recommandé	S150-95 Resilient Tile Spray, , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	



Emballage

Pièces Par Carton	24 pcs	
Surface Par Carton	35.65 sq ft	3.31 sq m
Poids Par Carton	41.5 lbs	18.82 kg

Méthodes d'Installation Conseillées



Coordination Des Produits

LVT: Uncommon Ground 4"

Performance + Tests Et Essai

Charge Statique (Astm F970)	Passes (Modified), *1500 lbs Passes Passes Passes Passes, Class I >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes	Ce Test Est Destiné À Comparer Les Propriétés Relatives De Différents Styles Et Constructions. Les Résultats Sont Basés Sur Un Test De Laboratoire Et Utilisés À Des Fins De Comparaison - La Limite De Charge Réelle Peut Varier.
Poinçonnement Rémanent (Astm F1914)		
Résistance À La Chaleur (Astm F1514)		
Résistance À La Lumière (Astm F1515)		
Résistance Chimique (Astm F925)		
Essai Au Panneau Radiant (Astm E648)		
Coefficient De Frottement (Astm D2407, Résistance Au Glissement)		Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)
[Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient](#)

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw’s diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Attributs + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure FloorScore® Agréé
Indoor Air Quality	
Climate Impact	
Environmental Product Declaration (EPD)	Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017 6.05 Kg Co ₂ /M ² 0% (Pre-Consumer 0% Post-Consumer 0%)
Embodied Carbon (Cradle to Gate)	
Total Recycled Content	
Global Product Assessment	CE Marking (EN 14041) Certifié Par Un Tiers Country of Origin Imported

Contribution Au Certificat Vert Leed

« Crédit MR : Divulgateion et optimisation des produits de construction
« Crédit MR : Divulgateion et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Health Product Declaration (HPD) | 100 Ppm Disclosure
3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore Certified

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.


Available Colorways




Provence 02140
LRV 33.9 | L* 64.91
V2 - Slight Variation




Driftwood 02150
V2 - Slight Variation




Sand Dune 02160
V2 - Slight Variation



Gallery Maple 02200
V2 - Slight Variation




French Grey 02500
LRV 19.1 | L* 50.82
V3 - Moderate Variation




White Oak 02506
V2 - Slight Variation



Zen 02520
V2 - Slight Variation



Teak Light 02530
V3 - Moderate Variation




Brazilian Chry 02534
V3 - Moderate Variation




Telluride 02540
V4 - Substantial Variation




Teak Green 02544
V2 - Slight Variation




Skyline 02560
V2 - Slight Variation



Cikel Cherry 02571
V2 - Slight Variation




Asian Mahogany 02572
V2 - Slight Variation



Chocolate Chry 02573
V2 - Slight Variation



Whiskey Barrel 02580
V2 - Slight Variation



Olivewood 02700
V3 - Moderate Variation



Bamboo Natural 02701
V2 - Slight Variation



Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

