

Uncommon Ground 6"

Collection	Uncommon Ground	
Style Number	0188V	
Construction	Heavy Commercial Luxury Vinyl Tile	
Class / ASTM F1700	Class III, Type B	
Finish	ExoGuard®	
	U.s.	Metric
Nominal Dimensions	6 in w x 36 in l	15 cm w x 92 cm l
Actual Dimensions	5.91 in w x 36.22 in l	15.01 cm w x 92.00 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.118 in	3 mm
Edge Profile	Squared Edge	
Installation Type	Dry Back	
Installation	Direct Glue	
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

Packaging

Pieces Per Carton	24 pcs	
Area Per Carton	35.65 sq ft	3.31 sq m
Weight Per Carton	41.5 lbs	18.82 kg



Recommended Installation Method



Coordinating Products

LVT: Uncommon Ground 4"

Performance + Testing

Residual Indentation (Astm F1914)	Passes
Resistance To Heat (Astm F1514)	Passes
Resistance To Light (Astm F1515)	Passes
Resistance To Chemicals (Astm F925)	Passes
Coefficient Of Friction (Astm D2407, Slip Resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited
[Commercial Limited Underbed Bond Warranty S150/4151/Lokworx+ Resilient](#)

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Material Health & Environmental Certifications

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 100 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

Embodied Carbon (Cradle to Gate)

6.05 Kg CO₂/M²

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certified
CE Marking (EN 14041) | 3rd Party Certified
Country of Origin | Imported

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization
Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

EQ Credit: Low Emitting Materials
Option 1: Product Category Calculations

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

[Installation Guidelines](#)

Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways

 <div>Provence 02140 LRV 33.9 V2 - Slight Variation</div>	 <div>Driftwood 02150 V2 - Slight Variation</div>	 <div>Sand Dune 02160 V2 - Slight Variation</div>	 <div>Gallery Maple 02200 V2 - Slight Variation</div>	 <div>French Grey 02500 LRV 19.1 V3 - Moderate Variation</div>	 <div>White Oak 02506 V2 - Slight Variation</div>
 <div>Zen 02520 V2 - Slight Variation</div>	 <div>Teak Light 02530 V3 - Moderate Variation</div>	 <div>Brazilian Chry 02534 V3 - Moderate Variation</div>	 <div>Telluride 02540 V4 - Substantial Variation</div>	 <div>Teak Green 02544 V2 - Slight Variation</div>	 <div>Skyline 02560 V2 - Slight Variation</div>
 <div>Cikel Cherry 02571 V2 - Slight Variation</div>	 <div>Asian Mahogany 02572 V2 - Slight Variation</div>	 <div>Chocolate Chry 02573 V2 - Slight Variation</div>	 <div>Whiskey Barrel 02580 V2 - Slight Variation</div>	 <div>Olivewood 02700 V3 - Moderate Variation</div>	 <div>Bamboo Natural 02701 V2 - Slight Variation</div>
 <div>Bamboo Coffee 02702 V2 - Slight Variation</div>	 <div>Heritage 02710 V2 - Slight Variation</div>	 <div>Adirondack 02720 LRV 10.2 V2 - Slight Variation</div>	 <div>Gallery Walnut 02740 V3 - Moderate Variation</div>	 <div>Colonial 02750 V2 - Slight Variation</div>	 <div>Ceylon 02760 V2 - Slight Variation</div>

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.



