

Naturelife Wood II


Style Number	0002V	
Welding Rod Style Number	353VS	
Construction	Commercial Heterogeneous Sheet With Fiberglass	
class	Type I, Grade 1, Class B	
Backing Class	4-ply fused backing system	
Finish	ExoGuard®	
	U.s.	Metric
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Product Thickness	0.087 in	2.2 mm
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Packaging

Actual Roll Size	6.00 ft w x 75.00 ft l	1.83 m w x 22.86 m l
Area Per Roll	50 sy/roll	41.81 sq m/roll
Weight Per Roll	282.2 lbs	128 kg



Recommended Installation Method



performance + testing

static load (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
residual indentation (ASTM F1914)	Passes	
Flexibility (ASTM F137)	Passes	
resistance to heat (ASTM F1514)	Passes	
resistance to light (ASTM F1515)	Passes	
resistance to chemicals (ASTM F925)	Passes	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
radiant panel (ASTM E648)	Passes, Class I	
coefficient of friction (ASTM D2407, slip resistance)		

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

- 15 Year Commercial Limited
- Commercial 15 Year Underbed Bond Warranty

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Attributes + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.4 Kg Co <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	
	CE Marking (EN 14041)   3rd Party Certified
	Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	
EQ Credit: Low Emitting Materials	FloorScore® Certified
Option 1: Product Category Calculations	

Installation Guidelines

Maintenance Guidelines





















Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.


Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways


 <div>Fumed Wenge 02421 V3 - Moderate Variation Weldrod 12595</div>	 <div>Traditional Cherry 05301 V2 - Slight Variation Weldrod 05301</div>	 <div>American Cherry 05303 V3 - Moderate Variation Weldrod 05303</div>	 <div>Light Maple 05304 V2 - Slight Variation Weldrod 05304</div>	 <div>Brazilian Cherry 05306 V2 - Slight Variation Weldrod 09446</div>	 <div>Chocolate Cherry 07716 V2 - Slight Variation Weldrod 09446</div>
 <div>Weathered Cherry 07717 V2 - Slight Variation Weldrod 06303</div>	 <div>Japanese Oak-Green 07720 V2 - Slight Variation Weldrod 05254</div>	 <div>Teak 08265 V3 - Moderate Variation Weldrod 08127</div>	 <div>Grey Teak 08266 V2 - Slight Variation Weldrod 07329</div>	 <div>Apple 08311 V4 - Substantial Variation Weldrod 05301</div>	 <div>Raw Ash 08316 V2 - Slight Variation Weldrod 02027</div>
 <div>Antique Mahogany 09446 V3 - Moderate Variation Weldrod 09446</div>	 <div>Rosewood 09561 V2 - Slight Variation Weldrod 02023</div>	 <div>Stained Walnut 09572 V4 - Substantial Variation Weldrod 01823</div>	 <div>Natural Walnut 09573 V4 - Substantial Variation Weldrod 02026</div>	 <div>Bleached Walnut 09574 V4 - Substantial Variation Weldrod 02019</div>	 <div>Reclaimed Hickory 09633 V2 - Slight Variation Weldrod 09633</div>
 <div>Young Hickory 09634 V3 - Moderate Variation Weldrod 09634</div>	 <div>Vintage Hickory 09635 V3 - Moderate Variation Weldrod 09635</div>				

Color and Visual Variation Index


Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1


Uniform Appearance

V2

Slight Variation

V3

Moderate Variation

V4

Substantial Variation

