

Naturelife Wood II


Número De Estilo	0002V	
Número De Estilo De Barra De Soldadura	353VS	
Construcción	Manta Vinílica Comercial Heterogénea Con Fibra De Vidrio	
clase	Type I, Grade 1, Class B	
Clase De Base	Sistema de base fusionado de 4 capas	
Terminación	ExoGuard®	
	U.s.	Metric
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.087 in	2.2 mm
Adhesivo Recomendado	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Embalaje

Tamaño Real Del Rollo	6.00 ft w x 75.00 ft l	1.83 m w x 22.86 m l
Área Por Rollo	50 sy/roll	41.81 sq m/roll
Peso Por Rollo	282.2 lbs	128 kg



Método De Instalación Recomendado



desempeño + pruebas

carga estática (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
margen adicional residual (ASTM F1914)	Passes	
Flexibility (ASTM F137)	Passes	
resistencia al calor (ASTM F1514)	Passes	
resistencia a la luz (ASTM F1515)	Passes	
resistencia a productos químicos (ASTM F925)	Passes	Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.
panel radiante (ASTM E648)	Passes, Class I	
coeficiente de fricción (ASTM D2407, resistencia al deslizamiento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Garantías

[15 Años Limitado A Uso Comercial](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificaciones

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certificado
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.4 Kg Co <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041)   Certificado Tercerizado
	Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>FloorScore Certificate</b>


Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	<b>FloorScore® Certified</b>
Installation Guidelines	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information.


### Available Colorways



Fumed Wenge 02421  
V3 - Moderate Variation  
Weldrod 12595




Traditional Cherry 05301  
V2 - Slight Variation  
Weldrod 05301




American Cherry 05303  
V3 - Moderate Variation  
Weldrod 05303



Light Maple 05304  
V2 - Slight Variation  
Weldrod 05304



Brazilian Cherry 05306  
V2 - Slight Variation  
Weldrod 09446




Chocolate Cherry 07716  
V2 - Slight Variation  
Weldrod 09446



Weathered Cherry 07717  
V2 - Slight Variation  
Weldrod 06303



Japanese Oak-Green  
07720  
V2 - Slight Variation  
Weldrod 05254



Teak 08265  
V3 - Moderate Variation  
Weldrod 08127




Grey Teak 08266  
V2 - Slight Variation  
Weldrod 07329




Apple 08311  
V4 - Substantial Variation  
Weldrod 05301




Raw Ash 08316  
V2 - Slight Variation  
Weldrod 02027




Antique Mahogany 09446  
V3 - Moderate Variation  
Weldrod 09446




Rosewood 09561  
V2 - Slight Variation  
Weldrod 02023



Stained Walnut 09572  
V4 - Substantial Variation  
Weldrod 01823



Natural Walnut 09573  
V4 - Substantial Variation  
Weldrod 02026



Bleached Walnut 09574  
V4 - Substantial Variation  
Weldrod 02019



Reclaimed Hickory 09633  
V2 - Slight Variation  
Weldrod 09633



Young Hickory 09634  
V3 - Moderate Variation  
Weldrod 09634



Vintage Hickory 09635  
V3 - Moderate Variation  
Weldrod 09635

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

