

Naturelife Wood II


Número De Estilo	0002V	
Número De Estilo De Barra De Soldadura	353VS	
Construcción	Manta Vinílica Comercial Heterogénea Con Fibra De Vidrio	
clase	Type I, Grade 1, Class B	
Clase De Base	Sistema de base fusionado de 4 capas	
Terminación	ExoGuard®	
	U.s.	Metric
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.087 in	2.2 mm
Adhesivo Recomendado	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	



Embalaje

Tamaño Real Del Rollo	6.00 ft w x 75.00 ft l	1.83 m w x 22.86 m l
Área Por Rollo	50 sy/roll	41.81 sq m/roll
Peso Por Rollo	282.2 lbs	128 kg

Método De Instalación Recomendado



desempeño + pruebas

carga estática (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
margen adicional residual (ASTM F1914)	Passes	
Flexibility (ASTM F137)	Passes	
resistencia al calor (ASTM F1514)	Passes	
resistencia a la luz (ASTM F1515)	Passes	
resistencia a productos químicos (ASTM F925)	Passes	Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.
panel radiante (ASTM E648)	Passes, Class I	
coeficiente de fricción (ASTM D2407, resistencia al deslizamiento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Garantías

[Commercial 15 Year Underbed Bond Warranty](#)
[15 Años Limitado A Uso Comercial](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificaciones

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.4 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	
	CE Marking (EN 14041) Certificado Tercerizado
	Country of Origin Imported





















WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Contribución Para Créditos Leed





Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	FloorScore® Certified
Installation Guidelines	<p>Please visit www.shawcontract.com for the most current warranty information.</p> <p>Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.</p> <p>This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.</p> <p>Visit shawcontract.com/testing for more information.</p>
Maintenance Guidelines	

Available Colorways

					
Fumed Wenge 02421 V3 - Moderate Variation Weldrod 12595	Traditional Cherry 05301 V2 - Slight Variation Weldrod 05301	American Cherry 05303 V3 - Moderate Variation Weldrod 05303	Light Maple 05304 V2 - Slight Variation Weldrod 05304	Brazilian Cherry 05306 V2 - Slight Variation Weldrod 09446	Chocolate Cherry 07716 V2 - Slight Variation Weldrod 09446
					
Weathered Cherry 07717 V2 - Slight Variation Weldrod 06303	Japanese Oak-Green 07720 V2 - Slight Variation Weldrod 05254	Teak 08265 V3 - Moderate Variation Weldrod 08127	Grey Teak 08266 V2 - Slight Variation Weldrod 07329	Apple 08311 V4 - Substantial Variation Weldrod 05301	Raw Ash 08316 V2 - Slight Variation Weldrod 02027
					
Antique Mahogany 09446 V3 - Moderate Variation Weldrod 09446	Rosewood 09561 V2 - Slight Variation Weldrod 02023	Stained Walnut 09572 V4 - Substantial Variation Weldrod 01823	Natural Walnut 09573 V4 - Substantial Variation Weldrod 02026	Bleached Walnut 09574 V4 - Substantial Variation Weldrod 02019	Reclaimed Hickory 09633 V2 - Slight Variation Weldrod 09633
					
Young Hickory 09634 V3 - Moderate Variation Weldrod 09634	Vintage Hickory 09635 V3 - Moderate Variation Weldrod 09635				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1 	V2 	V3 	V4 
Uniform Appearance	Slight Variation	Moderate Variation	Substantial Variation

