

Naturelife Wood II


Número De Estilo	0002V	
Número De Estilo De Barra De Soldadura	353VS	
Construcción	Manta Vinílica Comercial Heterogénea Con Fibra De Vidrio	
clase	Type I, Grade 1, Class B	
Clase De Base	Sistema de base fusionado de 4 capas	
Terminación	ExoGuard®	
	U.s.	Metric
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.087 in	2.2 mm
Adhesivo Recomendado	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	



Embalaje

Tamaño Real Del Rollo	6.00 ft w x 75.00 ft l	1.83 m w x 22.86 m l
Área Por Rollo	50 sy/roll	41.81 sq m/roll
Peso Por Rollo	282.2 lbs	128 kg

Método De Instalación Recomendado



Desempeño + Pruebas

Carga Estática (Astm F970)	Passes (Modified), *1500 lbs	Esta Prueba Tiene La Función De Comparar Propiedades Relativas De Diferentes Estilos Y Construcciones. Los Resultados Se Basan En Una Prueba De Laboratorio Y Se Utilizan Con Fines Comparativos: El Límite De Carga En La Vida Real Puede Variar.
Margen Adicional Residual (Astm F1914)	Passes	
Flexibilidad (Astm F137)	Passes	
Resistencia Al Calor (Astm F1514)	Passes	
Resistencia A La Luz (Astm F1515)	Passes	
Resistencia A Productos Químicos (Astm F925)	Passes	
Panel Radiante (Astm E648)	Passes, Class I	
Coefficiente De Fricción (Astm D2407, Resistencia Al Deslizamiento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

[15 Años Limitado A Uso Comercial](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.





















Atributos + Certificaciones

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) Certificado Tercerizado
	Country of Origin Imported

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	FloorScore Certified
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.
	Visit shawcontract.com/testing for more information.

Available Colorways

 <div>Fumed Wenge 02421 V3 - Moderate Variation Weldrod 12595</div>	 <div>Traditional Cherry 05301 V2 - Slight Variation Weldrod 05301</div>	 <div>American Cherry 05303 V3 - Moderate Variation Weldrod 05303</div>	 <div>Light Maple 05304 V2 - Slight Variation Weldrod 05304</div>	 <div>Brazilian Cherry 05306 V2 - Slight Variation Weldrod 09446</div>	 <div>Chocolate Cherry 07716 V2 - Slight Variation Weldrod 09446</div>
 <div>Weathered Cherry 07717 V2 - Slight Variation Weldrod 06303</div>	 <div>Japanese Oak-Green 07720 V2 - Slight Variation Weldrod 05254</div>	 <div>Teak 08265 V3 - Moderate Variation Weldrod 08127</div>	 <div>Grey Teak 08266 V2 - Slight Variation Weldrod 07329</div>	 <div>Apple 08311 V4 - Substantial Variation Weldrod 05301</div>	 <div>Raw Ash 08316 V2 - Slight Variation Weldrod 02027</div>
 <div>Antique Mahogany 09446 V3 - Moderate Variation Weldrod 09446</div>	 <div>Rosewood 09561 V2 - Slight Variation Weldrod 02023</div>	 <div>Stained Walnut 09572 V4 - Substantial Variation Weldrod 01823</div>	 <div>Natural Walnut 09573 V4 - Substantial Variation Weldrod 02026</div>	 <div>Bleached Walnut 09574 V4 - Substantial Variation Weldrod 02019</div>	 <div>Reclaimed Hickory 09633 V2 - Slight Variation Weldrod 09633</div>
 <div>Young Hickory 09634 V3 - Moderate Variation Weldrod 09634</div>	 <div>Vintage Hickory 09635 V3 - Moderate Variation Weldrod 09635</div>				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

