

Naturelife Wood II


Numéro De Style	0002V	
Référence De La Baguette De Soudure	353VS	
Construction	Rouleau Hétérogène Commerciale	
classe	Type I, Grade 1, Class B	
Classe d'Endos	Endos fusionné à 4 plis	
Finition	ExoGuard®	
	Impérial	Métrique
Épaisseur De La Couche d'Usure	20 mil (0.02 in)	0.51 mm
Épaisseur Générale Du Produit	0.087 in	2.2 mm
Adhésif Recommandé	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	



Emballage

Dimensions Réelles Du Rouleau	6.00 ft w x 75.00 ft l	1.83 m w x 22.86 m l
Surface Par Rouleau	50 sy/roll	41.81 sq m/roll
Poids Par Rouleau	282.2 lbs	128 kg

Méthodes d'Installation Conseillées



Performance + Tests Et Essai

Charge Statique (Astm F970)	Passes (Modified), *1500 lbs	Ce Test Est Destiné À Comparer Les Propriétés Relatives De Différents Styles Et Constructions. Les Résultats Sont Basés Sur Un Test De Laboratoire Et Utilisés À Des Fins De Comparaison - La Limite De Charge Réelle Peut Varier.
Poinçonnement Rémanent (Astm F1914)	Passes	
Souplesse (Astm F137)	Passes	
Résistance À La Chaleur (Astm F1514)	Passes	
Résistance À La Lumière (Astm F1515)	Passes	
Résistance Chimique (Astm F925)	Passes	
Essai Au Panneau Radiant (Astm E648)	Passes, Class I	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces
Coefficient De Frottement (Astm D2407, Résistance Au Glissement)		

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.





















Attributs + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure FloorScore® Agréé
Indoor Air Quality	
Climate Impact	
Environmental Product Declaration (EPD)	Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017 0% (Pre-Consumer 0% Post-Consumer 0%)
Total Recycled Content	
Global Product Assessment	
CE Marking (EN 14041) Certifié Par Un Tiers Country of Origin Imported	

Contribution Au Certificat Vert Leed





« Crédit MR : Divulgateion et optimisation des produits de construction	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 FloorScore Certified Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs. Visit shawcontract.com/testing for more information.
Crédit EQ : matériaux faibles émissions	
Installation Guidelines	
Maintenance Guidelines	

Available Colorways

					
Fumed Wenge 02421 V3 - Moderate Variation Weldrod 12595	Traditional Cherry 05301 V2 - Slight Variation Weldrod 05301	American Cherry 05303 V3 - Moderate Variation Weldrod 05303	Light Maple 05304 V2 - Slight Variation Weldrod 05304	Brazilian Cherry 05306 V2 - Slight Variation Weldrod 09446	Chocolate Cherry 07716 V2 - Slight Variation Weldrod 09446
					
Weathered Cherry 07717 V2 - Slight Variation Weldrod 06303	Japanese Oak-Green 07720 V2 - Slight Variation Weldrod 05254	Teak 08265 V3 - Moderate Variation Weldrod 08127	Grey Teak 08266 V2 - Slight Variation Weldrod 07329	Apple 08311 V4 - Substantial Variation Weldrod 05301	Raw Ash 08316 V2 - Slight Variation Weldrod 02027
					
Antique Mahogany 09446 V3 - Moderate Variation Weldrod 09446	Rosewood 09561 V2 - Slight Variation Weldrod 02023	Stained Walnut 09572 V4 - Substantial Variation Weldrod 01823	Natural Walnut 09573 V4 - Substantial Variation Weldrod 02026	Bleached Walnut 09574 V4 - Substantial Variation Weldrod 02019	Reclaimed Hickory 09633 V2 - Slight Variation Weldrod 09633
					
Young Hickory 09634 V3 - Moderate Variation Weldrod 09634	Vintage Hickory 09635 V3 - Moderate Variation Weldrod 09635				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1	V2	V3	V4
			
Uniform Appearance	Slight Variation	Moderate Variation	Substantial Variation

