

## Naturelife Wood II

Número Do Produto	<b>0002V</b>	
Número Do Estilo Da Haste De Soldagem	<b>353VS</b>	
Construção	<b>Manta Comercial Heterogênea Com Fibra De Vidro</b>	
classe	<b>Type I, Grade 1, Class B</b>	
Tipo De Base	<b>Sistema de revestimento fundido de 4 camadas</b>	
Acabamento	<b>ExoGuard®</b>	
	U.s.	Metric
Espessura Da Camada De Uso	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Espessura Total Do Produto	<b>0.087 in</b>	<b>2.2 mm</b>
Adesivo Recomendado	<b>S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon</b>	

### Empacotamento

Tamanho Real Do Rolo	<b>6.00 ft w x 75.00 ft l</b>	<b>1.83 m w x 22.86 m l</b>
Área Por Rolo	<b>50 sy/roll</b>	<b>41.81 sq m/roll</b>
Peso Por Rolo	<b>282.2 lbs</b>	<b>128 kg</b>



### Método De Instalação Recomendado



Reverso

### desempenho + teste

carga estática (ASTM F970)	<b>Passes (Modified), *1500 lbs</b>	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
recuo residual (ASTM F1914)	<b>Passes</b>	
Flexibility (ASTM F137)	<b>Passes</b>	
resistência ao calor (ASTM F1514)	<b>Passes</b>	
resistência à luz (ASTM F1515)	<b>Passes</b>	
resistência a produtos químicos (ASTM F925)	<b>Passes</b>	
painel radiante (ASTM E648)	<b>Passes, Class I</b>	
coeficiente de atrito (ASTM D2407, resistência ao deslizamento)	<b>≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces</b>	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

### Garantias

[Commercial 15 Year Underbed Bond Warranty](#)

[15 Anos Comercial Limitada](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificações

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.4 Kg Co <sub>2</sub> /M <sup>2</sup>
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041)   Certificado 3rd Party
	Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>FloorScore Certificate</b>

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	<b>FloorScore® Certified</b>
Crédito de EQ: Materiais de baixa emissão	
Opção 1: cálculos de categoria de produto	

Installation Guidelines

Maintenance Guidelines





















Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.





Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

### Available Colorways

					
Fumed Wenge 02421 V3 - Moderate Variation Weldrod 12595	Traditional Cherry 05301 V2 - Slight Variation Weldrod 05301	American Cherry 05303 V3 - Moderate Variation Weldrod 05303	Light Maple 05304 V2 - Slight Variation Weldrod 05304	Brazilian Cherry 05306 V2 - Slight Variation Weldrod 09446	Chocolate Cherry 07716 V2 - Slight Variation Weldrod 09446
					
Weathered Cherry 07717 V2 - Slight Variation Weldrod 06303	Japanese Oak-Green 07720 V2 - Slight Variation Weldrod 05254	Teak 08265 V3 - Moderate Variation Weldrod 08127	Grey Teak 08266 V2 - Slight Variation Weldrod 07329	Apple 08311 V4 - Substantial Variation Weldrod 05301	Raw Ash 08316 V2 - Slight Variation Weldrod 02027
					
Antique Mahogany 09446 V3 - Moderate Variation Weldrod 09446	Rosewood 09561 V2 - Slight Variation Weldrod 02023	Stained Walnut 09572 V4 - Substantial Variation Weldrod 01823	Natural Walnut 09573 V4 - Substantial Variation Weldrod 02026	Bleached Walnut 09574 V4 - Substantial Variation Weldrod 02019	Reclaimed Hickory 09633 V2 - Slight Variation Weldrod 09633
					
Young Hickory 09634 V3 - Moderate Variation Weldrod 09634	Vintage Hickory 09635 V3 - Moderate Variation Weldrod 09635				

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1 	V2 	V3 	V4 
Uniform Appearance	Slight Variation	Moderate Variation	Substantial Variation

