

Naturelife Wood II


Número Do Produto	0002V	
Número Do Estilo Da Haste De Soldagem	353VS	
Construção	Manta Comercial Heterogênea Com Fibra De Vidro	
classe	Type I, Grade 1, Class B	
Tipo De Base	Sistema de revestimento fundido de 4 camadas	
Acabamento	ExoGuard®	
	U.s.	Metric
Espessura Da Camada De Uso	20 mil (0.02 in)	0.51 mm
Espessura Total Do Produto	0.087 in	2.2 mm
Adesivo Recomendado	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	



Empacotamento

Tamanho Real Do Rolo	6.00 ft w x 75.00 ft l	1.83 m w x 22.86 m l
Área Por Rolo	50 sy/roll	41.81 sq m/roll
Peso Por Rolo	282.2 lbs	128 kg

Método De Instalação Recomendado



Desempenho + Teste

Carga Estática (Astm F970)	Passes (Modified), *1500 lbs	Este Teste Tem Como Objetivo Comparar Propriedades Relativas De Diferentes Estilos E Construções. Os Resultados São Baseados Em Um Teste De Laboratório E Usados Para Fins Comparativos - O Limite De Carga Na Vida Real Pode Variar.
Recuo Residual (Astm F1914)	Passes	
Flexibilidade (Astm F137)	Passes	
Resistência Ao Calor (Astm F1514)	Passes	
Resistência À Luz (Astm F1515)	Passes	
Resistência A Produtos Químicos (Astm F925)	Passes	
Painel Radiante (Astm E648)	Passes, Class I	
Coefficiente De Atrito (Astm D2407, Resistência Ao Deslizamento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

15 Anos Comercial Limitada
Commercial 15 Year Underbed Bond Warranty

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificações

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) Certificado 3rd Party
	Country of Origin Imported


Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	FloorScore Certified
Crédito de EQ: Materiais de baixa emissão	
Opção 1: cálculos de categoria de produto	
Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.
	Visit shawcontract.com/testing for more information.


Available Colorways



Fumed Wenge 02421
V3 - Moderate Variation
Weldrod 12595




Traditional Cherry 05301
V2 - Slight Variation
Weldrod 05301




American Cherry 05303
V3 - Moderate Variation
Weldrod 05303



Light Maple 05304
V2 - Slight Variation
Weldrod 05304



Brazilian Cherry 05306
V2 - Slight Variation
Weldrod 09446




Chocolate Cherry 07716
V2 - Slight Variation
Weldrod 09446



Weathered Cherry 07717
V2 - Slight Variation
Weldrod 06303



Japanese Oak-Green
07720
V2 - Slight Variation
Weldrod 05254



Teak 08265
V3 - Moderate Variation
Weldrod 08127




Grey Teak 08266
V2 - Slight Variation
Weldrod 07329




Apple 08311
V4 - Substantial Variation
Weldrod 05301




Raw Ash 08316
V2 - Slight Variation
Weldrod 02027




Antique Mahogany 09446
V3 - Moderate Variation
Weldrod 09446




Rosewood 09561
V2 - Slight Variation
Weldrod 02023



Stained Walnut 09572
V4 - Substantial Variation
Weldrod 01823



Natural Walnut 09573
V4 - Substantial Variation
Weldrod 02026



Bleached Walnut 09574
V4 - Substantial Variation
Weldrod 02019



Reclaimed Hickory 09633
V2 - Slight Variation
Weldrod 09633



Young Hickory 09634
V3 - Moderate Variation
Weldrod 09634



Vintage Hickory 09635
V3 - Moderate Variation
Weldrod 09635

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

