

Naturelife Wood II

| | | |
|--------------------------|---|---------|
| Style Number | 0002V | |
| Welding Rod Style Number | 353VS | |
| Construction | Commercial Heterogeneous Sheet With Fibreglass | |
| Class / ASTM F1303 | Type I, Grade 1, Class B | |
| Backing Class | 4-ply fused backing system | |
| Finish | ExoGuard® | |
| | U.s. | Metric |
| Wear Layer Thickness | 20 mil (0.02 in) | 0.51 mm |
| Overall Thickness | 0.087 in | 2.2 mm |
| Recommended Adhesive | S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon | |

Packaging

| | | |
|------------------|------------------------|----------------------|
| Actual Roll Size | 6.00 ft w x 75.00 ft l | 1.83 m w x 22.86 m l |
| Area Per Roll | 50 sy/roll | 41.81 sq m/roll |
| Weight Per Roll | 282.2 lbs | 128 kg |



Recommended Installation Method



Performance + Testing

| | |
|---|---|
| Residual Indentation (Astm F1914) | Passes |
| Flexibility (Astm F137) | Passes |
| Resistance To Heat (Astm F1514) | Passes |
| Resistance To Light (Astm F1515) | Passes |
| Resistance To Chemicals (Astm F925) | Passes |
| Coefficient Of Friction (Astm D2407, Slip Resistance) | ≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Material Health & Environmental Certifications

| | |
|---|--|
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | FloorScore® Certified |
| | CE Marking (EN 14041) 3rd Party Certified |
| | Country of Origin Imported |

Green Leed Contribution Credit







| | |
|--|--|
| MR Credit: Building Product Disclosure and Optimization | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | FloorScore Certified |
| EQ Credit: Low Emitting Materials | |
| Option 1: Product Category Calculations | |
| Installation Guidelines | Please visit www.shawcontract.com for the most current warranty information. |
| Maintenance Guidelines | Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. |

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways


| | | | | | |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Fumed Wenge 02421 | Traditional Cherry 05301 | American Cherry 05303 | Light Maple 05304 | Brazilian Cherry 05306 | Chocolate Cherry 07716 |
| V3 - Moderate Variation | V2 - Slight Variation | V3 - Moderate Variation | V2 - Slight Variation | V2 - Slight Variation | V2 - Slight Variation |
| Weldrod 12595 | Weldrod 05301 | Weldrod 05303 | Weldrod 05304 | Weldrod 09446 | Weldrod 09446 |



Weathered Cherry 07717
V2 - Slight Variation
Weldrod 06303




Japanese Oak-Green 07720
V2 - Slight Variation
Weldrod 05254



Teak 08265
V3 - Moderate Variation
Weldrod 08127




Grey Teak 08266
V2 - Slight Variation
Weldrod 07329




Apple 08311
V4 - Substantial Variation
Weldrod 05301




Raw Ash 08316
V2 - Slight Variation
Weldrod 02027




Antique Mahogany 09446
V3 - Moderate Variation
Weldrod 09446




Rosewood 09561
V2 - Slight Variation
Weldrod 02023



Stained Walnut 09572
V4 - Substantial Variation
Weldrod 01823



Natural Walnut 09573
V4 - Substantial Variation
Weldrod 02026



Bleached Walnut 09574
V4 - Substantial Variation
Weldrod 02019



Reclaimed Hickory 09633
V2 - Slight Variation
Weldrod 09633



Young Hickory 09634
V3 - Moderate Variation
Weldrod 09634



Vintage Hickory 09635
V3 - Moderate Variation
Weldrod 09635

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

