

Naturelife Wood II

Style Number	0002V	
Welding Rod Style Number	353VS	
Construction	Commercial Heterogeneous Sheet With Fibreglass	
Class / ASTM F1303	Type I, Grade 1, Class B	
Backing Class	4-ply fused backing system	
Finish	ExoGuard®	
	U.s.	Metric
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.087 in	2.2 mm
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

Packaging

Actual Roll Size	6.00 ft w x 75.00 ft l	1.83 m w x 22.86 m l
Area Per Roll	50 sy/roll	41.81 sq m/roll
Weight Per Roll	282.2 lbs	128 kg



Recommended Installation Method



Reverse

Performance + Testing

Residual Indentation (Astm F1914)	Passes
Flexibility (Astm F137)	Passes
Resistance To Heat (Astm F1514)	Passes
Resistance To Light (Astm F1515)	Passes
Resistance To Chemicals (Astm F925)	Passes
Coefficient Of Friction (Astm D2407, Slip Resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited  
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Material Health & Environmental Certifications

Climate Impact

Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	FloorScore®   Certified CE Marking (EN 14041)   3rd Party Certified Country of Origin   Imported

Green Leed Contribution Credit







MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore Certified
Installation Guidelines	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways


					
Fumed Wenge 02421 V3 - Moderate Variation Weldrod 12595	Traditional Cherry 05301 V2 - Slight Variation Weldrod 05301	American Cherry 05303 V3 - Moderate Variation Weldrod 05303	Light Maple 05304 V2 - Slight Variation Weldrod 05304	Brazilian Cherry 05306 V2 - Slight Variation Weldrod 09446	Chocolate Cherry 07716 V2 - Slight Variation Weldrod 09446



Weathered Cherry 07717  
V2 - Slight Variation  
Weldrod 06303




Japanese Oak-Green 07720  
V2 - Slight Variation  
Weldrod 05254



Teak 08265  
V3 - Moderate Variation  
Weldrod 08127




Grey Teak 08266  
V2 - Slight Variation  
Weldrod 07329




Apple 08311  
V4 - Substantial Variation  
Weldrod 05301




Raw Ash 08316  
V2 - Slight Variation  
Weldrod 02027




Antique Mahogany 09446  
V3 - Moderate Variation  
Weldrod 09446




Rosewood 09561  
V2 - Slight Variation  
Weldrod 02023



Stained Walnut 09572  
V4 - Substantial Variation  
Weldrod 01823




Natural Walnut 09573  
V4 - Substantial Variation  
Weldrod 02026



Bleached Walnut 09574  
V4 - Substantial Variation  
Weldrod 02019



Reclaimed Hickory 09633  
V2 - Slight Variation  
Weldrod 09633



Young Hickory 09634  
V3 - Moderate Variation  
Weldrod 09634



Vintage Hickory 09635  
V3 - Moderate Variation  
Weldrod 09635

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

