

Naturelife Wood II

Style Number	0002V	
Welding Rod Style Number	353VS	
Construction	Commercial Heterogeneous Sheet With Fiberglass	
Class / ASTM F1303	Type I, Grade 1, Class B	
Backing Class	4-ply Fused Backing System	
Finish	ExoGuard®	
	U.S.	Metric
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.087 in	2.2 mm
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Resilient Tile 4 Gallon or 4151 Multi-Use Premium 4 Gallon	



Packaging

Actual Roll Size	6.00 ft w x 75.00 ft l	1.83 m w x 22.86 m l
Area per Roll	50 sy/roll	41.81 sq m/roll
Weight per Roll	282.2 lbs	128 kg

Recommended Installation Method



Performance + Testing

Static Load (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
Residual Indentation (ASTM F1914)	Passes	
Flexibility (ASTM F137)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Resistance to Light (ASTM F1515)	Passes	
Resistance to Chemicals (ASTM F925)	Passes	
Radiant Panel (ASTM E648)	Passes, Class I	
Coefficient of Friction (ASTM D2047, Slip Resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

- 15 Year Commercial Limited Warranty
- Commercial 15 Year Underbed Bond Warranty

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Material Health & Environmental Certifications

Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	FloorScore® Certified GSA Approved CE Marking (EN 14041) 3rd Party Certified Country of Origin Imported

WELL V2 Contribution Credit





















X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization	FloorScore Certificate

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore Certified





Installation Guidelines	
Maintenance Guidelines	Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs. Visit shawcontract.com/testing for more information.

Available Colorways

					
Fumed Wenge 02421 V3 - Moderate Variation Weldrod 12595	Traditional Cherry 05301 V2 - Slight Variation Weldrod 05301	American Cherry 05303 V3 - Moderate Variation Weldrod 05303	Light Maple 05304 V2 - Slight Variation Weldrod 05304	Brazilian Cherry 05306 V2 - Slight Variation Weldrod 09446	Chocolate Cherry 07716 V2 - Slight Variation Weldrod 09446
					
Weathered Cherry 07717 V2 - Slight Variation Weldrod 06303	Japanese Oak-Green 07720 V2 - Slight Variation Weldrod 05254	Teak 08265 V3 - Moderate Variation Weldrod 08127	Grey Teak 08266 V2 - Slight Variation Weldrod 07329	Apple 08311 V4 - Substantial Variation Weldrod 05301	Raw Ash 08316 V2 - Slight Variation Weldrod 02027
					
Antique Mahogany 09446 V3 - Moderate Variation Weldrod 09446	Rosewood 09561 V2 - Slight Variation Weldrod 02023	Stained Walnut 09572 V4 - Substantial Variation Weldrod 01823	Natural Walnut 09573 V4 - Substantial Variation Weldrod 02026	Bleached Walnut 09574 V4 - Substantial Variation Weldrod 02019	Reclaimed Hickory 09633 V2 - Slight Variation Weldrod 09633
					
Young Hickory 09634 V3 - Moderate Variation Weldrod 09634	Vintage Hickory 09635 V3 - Moderate Variation Weldrod 09635				

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1 	V2 	V3 	V4 
Uniform Appearance	Slight Variation	Moderate Variation	Substantial Variation

