

Rexcourt Sheet


Style Number	0004V	
Welding Rod Style Number	021VS	
Construction	Commercial Heterogeneous Sheet With Fiberglass	
class		
Backing Class	Closed Cell Foam	
Finish	UV Urethane	
	U.s.	Metric
Wear Layer Thickness	39 mil (0.039 in)	0.99 mm
Overall Product Thickness	0.256 in	6.5 mm
Installation Type	Dry Back	
Recommended Adhesive	4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Packaging

Actual Roll Size	5.91 ft w x 49.20 ft l	1.80 m w x 15.00 m l
Area Per Roll	32.22 sy/roll	26.94 sq m/roll
Weight Per Roll	253.6 lbs	115.03 kg



Recommended Installation Method



performance + testing

Flexibility (ASTM F137)	Passes
resistance to heat (ASTM F1514)	Passes
resistance to light (ASTM F1515)	Passes
resistance to chemicals (ASTM F925)	Passes
radiant panel (ASTM E648)	Passes, Class I
coefficient of friction (ASTM D2407, slip resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[10 Year Commercial Limited](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Attributes + Certifications

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.403 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) 3rd Party Certified Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore® Certified

Installation Guidelines

Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways



Golden Cherry 01451
V3 - Moderate Variation
Weldrod 01451



Indian Cherry 01452
V3 - Moderate Variation
Weldrod 01425



Noble Zelkova 01811
V3 - Moderate Variation
Weldrod 01811



Tiger Oak 01821
V3 - Moderate Variation
Weldrod 01821



Windsor Oak 01822
V3 - Moderate Variation
Weldrod 01452



Antique Oak 01823
V3 - Moderate Variation
Weldrod 01823



Grand Maple 02001
V3 - Moderate Variation
Weldrod 02001



Red 06200
V1 - Uniform Appearance
Weldrod 06200



Beige 06301
V1 - Uniform Appearance
Weldrod 06301



Gray 06303
V1 - Uniform Appearance
Weldrod 06303



Dark Blue 06400
V1 - Uniform Appearance
Weldrod 06400



Blue 06402
V1 - Uniform Appearance
Weldrod 06402



Sky Blue 06403
V1 - Uniform Appearance
Weldrod 06403



Yellow 06500
V1 - Uniform Appearance
Weldrod 06500



Dark Green 06606
V1 - Uniform Appearance
Weldrod 06606



Orange 06901
V1 - Uniform Appearance
Weldrod 06901

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

