

Rexcourt Sheet

| | | |
|---------------------------|---|---------|
| Style Number | 0004V | |
| Welding Rod Style Number | 021VS | |
| Construction | Commercial Heterogeneous Sheet With Fiberglass | |
| class | | |
| Backing Class | Closed Cell Foam | |
| Finish | UV Urethane | |
| | U.s. | Metric |
| Wear Layer Thickness | 39 mil (0.039 in) | 0.99 mm |
| Overall Product Thickness | 0.256 in | 6.5 mm |
| Installation Type | Dry Back | |
| Recommended Adhesive | 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon | |

Packaging

| | | |
|------------------|------------------------|----------------------|
| Actual Roll Size | 5.91 ft w x 49.20 ft l | 1.80 m w x 15.00 m l |
| Area Per Roll | 32.22 sy/roll | 26.94 sq m/roll |
| Weight Per Roll | 253.6 lbs | 115.03 kg |



Recommended Installation Method



Reverse

performance + testing

| | |
|---|---|
| Flexibility (ASTM F137) | Passes |
| resistance to heat (ASTM F1514) | Passes |
| resistance to light (ASTM F1515) | Passes |
| resistance to chemicals (ASTM F925) | Passes |
| radiant panel (ASTM E648) | Passes, Class I |
| coefficient of friction (ASTM D2407, slip resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[10 Year Commercial Limited](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Attributes + Certifications

| | |
|---|--|
| Health & Wellbeing | |
| Indoor Air Quality | FloorScore® Certified |
| Climate Impact | |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate) | 9.403 Kg Co ₂ /M ² |
| Total Recycled Content | 0% (Pre-Consumer 0% Post-Consumer 0%) |
| Global Product Assessment | CE Marking (EN 14041) 3rd Party Certified |
| | Country of Origin Imported |

WELL V2 Contribution Credit

| | |
|--|--|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition | Absence of Asbestos |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt | Absence of Heavy Metals |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt | Absence of Halogenated Flame Retardants |
| Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt | Ortho-Phthalates |
| X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt | FloorScore Certificate |

Green Leed Contribution Credit

| | |
|---|---|
| MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| EQ Credit: Low Emitting Materials Option 1: Product Category Calculations | FloorScore® Certified |

Installation Guidelines

Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
Visit shawcontract.com/testing for more information.

Available Colorways

| | | | | | |
|---|--|--|---|---|---|
|  |  |  |  |  |  |
| Golden Cherry 01451 V3 - Moderate Variation Weldrod 01451 | Indian Cherry 01452 V3 - Moderate Variation Weldrod 01425 | Noble Zelkova 01811 V3 - Moderate Variation Weldrod 01811 | Tiger Oak 01821 V3 - Moderate Variation Weldrod 01821 | Windsor Oak 01822 V3 - Moderate Variation Weldrod 01452 | Antique Oak 01823 V3 - Moderate Variation Weldrod 01823 |
|  |  |  |  |  |  |
| Grand Maple 02001 V3 - Moderate Variation Weldrod 02001 | Red 06200 V1 - Uniform Appearance Weldrod 06200 | Beige 06301 V1 - Uniform Appearance Weldrod 06301 | Gray 06303 V1 - Uniform Appearance Weldrod 06303 | Dark Blue 06400 V1 - Uniform Appearance Weldrod 06400 | Blue 06402 V1 - Uniform Appearance Weldrod 06402 |
|  |  |  |  | | |
| Sky Blue 06403 V1 - Uniform Appearance Weldrod 06403 | Yellow 06500 V1 - Uniform Appearance Weldrod 06500 | Dark Green 06606 V1 - Uniform Appearance Weldrod 06606 | Orange 06901 V1 - Uniform Appearance Weldrod 06901 | | |

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

