

Rexcourt Sheet


|                          |   |         |
|--------------------------|---|---------|
| Style Number             | 0004V   |         |
| Welding Rod Style Number | 021VS   |         |
| Construction             | Commercial Heterogeneous Sheet With Fiberglass  |         |
| Backing Class            | Closed Cell Foam  |         |
| Finish                   | UV Urethane   |         |
|                          | U.S.  | Metric  |
| Wear Layer Thickness     | 39 mil (0.039 in)   | 0.99 mm |
| Overall Thickness        | 0.256 in  | 6.5 mm  |
| Installation Type        | Dry Back  |         |
| Recommended Adhesive     | 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon |         |

Packaging

|                  |                        |                      |
|------------------|------------------------|----------------------|
| Actual Roll Size | 5.91 ft w x 49.20 ft l | 1.80 m w x 15.00 m l |
| Area per Roll    | 32.22 sy/roll          | 26.94 sq m/roll      |
| Weight per Roll  | 253.6 lbs              | 115.03 kg            |



Recommended Installation Method



Performance + Testing

|   |   |
|---|---|
| Static Load (ASTM F970)                               | Passes  |
| Flexibility (ASTM F137)                               | Passes  |
| Resistance to Heat (ASTM F1514)                       | Passes  |
| Resistance to Light (ASTM F1515)                      | Passes  |
| Resistance to Chemicals (ASTM F925)                   | Passes  |
| Radiant Panel (ASTM E648)                             | Passes, Class I   |
| Coefficient of Friction (ASTM D2047, Slip Resistance) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[10 Year Commercial Limited Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Material Health & Environmental Certifications

|   |  |
|---|--|
| Health & Wellbeing                      |  |
| Indoor Air Quality                      | FloorScore®   Certified  |
| Climate Impact                          |  |
| Environmental Product Declaration (EPD) | 3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate)        | 9.403 Kg Co <sub>2</sub> /M <sup>2</sup>                                     |
| Total Recycled Content                  | 0% (Pre-Consumer 0%   Post-Consumer 0%)                                      |
| Global Product Assessment               | CE Marking (EN 14041)   3rd Party Certified<br>Country of Origin   Imported  |

WELL V2 Contribution Credit

|  |  |
|--|--|
| X01 Fundamental Material Precautions<br>Part 1: (C): Restrict Asbestos Precondition                    | <b>Absence of Asbestos</b>                     |
| X08 Hazardous Material Reduction<br>Part 1: Limit Hazardous Materials Optimization                     | <b>Absence of Heavy Metals</b>                 |
| X10 Volatile Compound Reduction<br>Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization   | <b>Absence of Halogenated Flame Retardants</b> |
| X10 Volatile Compound Reduction<br>Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization | <b>Ortho-Phthalates</b>                        |
| X11 Long Term Emissions Control<br>Part 2: Flooring Optimization                                       | <b>FloorScore Certificate</b>                  |

Leed v4 Contribution Credits

|   |   |
|---|---|
| MR Credit: Building Product Disclosure and Optimization<br>Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | <b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b> |
| EQ Credit: Low Emitting Materials<br>Option 1: Product Category Calculations  | <b>FloorScore Certified</b>   |

|                         |  |
|-------------------------|--|
| Installation Guidelines | Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.<br>Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.<br><br>This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.<br><br>Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information. |
| Maintenance Guidelines  |  |

Available Colorways

|   |  |  |   |   |   |
|---|--|--|---|---|---|
|   |   |   |   |  |  |
| Golden Cherry 01451<br>V3 - Moderate Variation<br>Weldrod 01451                   | Indian Cherry 01452<br>V3 - Moderate Variation<br>Weldrod 01425                    | Noble Zelkova 01811<br>V3 - Moderate Variation<br>Weldrod 01811                    | Tiger Oak 01821<br>V3 - Moderate Variation<br>Weldrod 01821                         | Windsor Oak 01822<br>V3 - Moderate Variation<br>Weldrod 01452                       | Antique Oak 01823<br>V3 - Moderate Variation<br>Weldrod 01823                       |
|   |   |   |   |  |  |
| Grand Maple 02001<br>V3 - Moderate Variation<br>Weldrod 02001                     | Red 06200<br>V1 - Uniform Appearance<br>Weldrod 06200                              | Beige 06301<br>V1 - Uniform Appearance<br>Weldrod 06301                            | Gray 06303<br>V1 - Uniform Appearance<br>Weldrod 06303                              | Dark Blue 06400<br>V1 - Uniform Appearance<br>Weldrod 06400                         | Blue 06402<br>V1 - Uniform Appearance<br>Weldrod 06402                              |
|  |  |  |  |   |   |
| Sky Blue 06403<br>V1 - Uniform Appearance<br>Weldrod 06403                        | Yellow 06500<br>V1 - Uniform Appearance<br>Weldrod 06500                           | Dark Green 06606<br>V1 - Uniform Appearance<br>Weldrod 06606                       | Orange 06901<br>V1 - Uniform Appearance<br>Weldrod 06901                            |   |   |

**Color and Visual Variation Index**

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

