

Rexcourt Sheet


Style Number	0004V	
Welding Rod Style Number	021VS	
Construction	Commercial Heterogeneous Sheet With Fibreglass	
Backing Class	Closed Cell Foam	
Finish	UV Urethane	
	U.s.	Metric
Wear Layer Thickness	39 mil (0.039 in)	0.99 mm
Overall Thickness	0.256 in	6.5 mm
Installation Type	Dry Back	
Recommended Adhesive	4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Packaging

Actual Roll Size	5.91 ft w x 49.20 ft l	1.80 m w x 15.00 m l
Area Per Roll	32.22 sy/roll	26.94 sq m/roll
Weight Per Roll	253.6 lbs	115.03 kg



Recommended Installation Method



Performance + Testing

Flexibility (ASTM F137)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
coefficient of friction (ASTM D2407, slip resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[10 Year Commercial Limited](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Material Health & Environmental Certifications

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.403 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) 3rd Party Certified Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore® Certified

Installation Guidelines

Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
Visit shawcontract.com/testing for more information.

Available Colorways

 Golden Cherry 01451 V3 - Moderate Variation Weldrod 01451	 Indian Cherry 01452 V3 - Moderate Variation Weldrod 01425	 Noble Zelkova 01811 V3 - Moderate Variation Weldrod 01811	 Tiger Oak 01821 V3 - Moderate Variation Weldrod 01821	 Windsor Oak 01822 V3 - Moderate Variation Weldrod 01452	 Antique Oak 01823 V3 - Moderate Variation Weldrod 01823
 Grand Maple 02001 V3 - Moderate Variation Weldrod 02001	 Red 06200 V1 - Uniform Appearance Weldrod 06200	 Beige 06301 V1 - Uniform Appearance Weldrod 06301	 Gray 06303 V1 - Uniform Appearance Weldrod 06303	 Dark Blue 06400 V1 - Uniform Appearance Weldrod 06400	 Blue 06402 V1 - Uniform Appearance Weldrod 06402
 Sky Blue 06403 V1 - Uniform Appearance Weldrod 06403	 Yellow 06500 V1 - Uniform Appearance Weldrod 06500	 Dark Green 06606 V1 - Uniform Appearance Weldrod 06606	 Orange 06901 V1 - Uniform Appearance Weldrod 06901		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

