

Rexcourt Sheet

Style Number	0004V	
Welding Rod Style Number	021VS	
Construction	Commercial Heterogeneous Sheet With Fiberglass	
Backing Class	Closed Cell Foam	
Finish	UV Urethane	
	U.S.	Metric
Wear Layer Thickness	39 mil (0.039 in)	0.99 mm
Overall Thickness	0.256 in	6.5 mm
Installation Type	Dry Back	
Recommended Adhesive	4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Packaging

Actual Roll Size	5.91 ft w x 49.20 ft l	1.80 m w x 15.00 m l
Area per Roll	32.22 sy/roll	26.94 sq m/roll
Weight per Roll	253.6 lbs	115.03 kg



Recommended Installation Method



Reverse

Performance + Testing

Static Load (ASTM F970)	Passes
Flexibility (ASTM F137)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Coefficient of Friction (ASTM D2047, Slip Resistance)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[10 Year Commercial Limited Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Material Health & Environmental Certifications

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) 3rd Party Certified Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization	FloorScore Certificate

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore Certified





Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	Visit shawcontract.com/testing for more information.

Available Colorways

					
Golden Cherry 01451 V3 - Moderate Variation Weldrod 01451	Indian Cherry 01452 V3 - Moderate Variation Weldrod 01425	Noble Zelkova 01811 V3 - Moderate Variation Weldrod 01811	Tiger Oak 01821 V3 - Moderate Variation Weldrod 01821	Windsor Oak 01822 V3 - Moderate Variation Weldrod 01452	Antique Oak 01823 V3 - Moderate Variation Weldrod 01823
					
Grand Maple 02001 V3 - Moderate Variation Weldrod 02001	Red 06200 V1 - Uniform Appearance Weldrod 06200	Beige 06301 V1 - Uniform Appearance Weldrod 06301	Gray 06303 V1 - Uniform Appearance Weldrod 06303	Dark Blue 06400 V1 - Uniform Appearance Weldrod 06400	Blue 06402 V1 - Uniform Appearance Weldrod 06402
					
Sky Blue 06403 V1 - Uniform Appearance Weldrod 06403	Yellow 06500 V1 - Uniform Appearance Weldrod 06500	Dark Green 06606 V1 - Uniform Appearance Weldrod 06606	Orange 06901 V1 - Uniform Appearance Weldrod 06901		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1		V2		V3		V4	
	Uniform Appearance		Slight Variation		Moderate Variation		Substantial Variation

