

Rexcourt Sheet


|  |   |         |
|--|---|---------|
| Número De Estilo                       | 0004V   |         |
| Número De Estilo De Barra De Soldadura | 021VS   |         |
| Construcción                           | Manta Vinílica Comercial Heterogénea Con Fibra De Vidrio  |         |
| clase                                  |   |         |
| Clase De Base                          | Espuma Celular Cerrada  |         |
| Terminación                            | UV Urethane   |         |
|  | U.s.  | Metric  |
| Desgaste De La Capa De Uso             | 39 mil (0.039 in)   | 0.99 mm |
| Espesor Total Del Producto             | 0.256 in  | 6.5 mm  |
| Installation Type                      | Dry Back  |         |
| Adhesivo Recomendado                   | 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon |         |

Embalaje

|                       |                        |                      |
|-----------------------|------------------------|----------------------|
| Tamaño Real Del Rollo | 5.91 ft w x 49.20 ft l | 1.80 m w x 15.00 m l |
| Área Por Rollo        | 32.22 sy/roll          | 26.94 sq m/roll      |
| Peso Por Rollo        | 253.6 lbs              | 115.03 kg            |



Método De Instalación Recomendado



desempeño + pruebas

|  |   |
|--|---|
| Flexibility (ASTM F137)  | Passes  |
| resistencia al calor (ASTM F1514)                                  | Passes  |
| resistencia a la luz (ASTM F1515)                                  | Passes  |
| resistencia a productos químicos (ASTM F925)                       | Passes  |
| panel radiante (ASTM E648)   | Passes, Class I   |
| coeficiente de fricción (ASTM D2407, resistencia al deslizamiento) | >0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

[10 Años Limitado A Uso Comercial](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificaciones

|   |   |
|---|---|
| Health & Wellbeing                      |   |
| Indoor Air Quality                      | FloorScore®   Certificado   |
| Climate Impact                          |   |
| Environmental Product Declaration (EPD) | Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017 |
| Embodied Carbon (Cradle to Gate)        | 9.403 Kg Co <sub>2</sub> /M <sup>2</sup>  |
| Total Recycled Content                  | 0% (Pre-Consumer 0%   Post-Consumer 0%)   |
| Global Product Assessment               | CE Marking (EN 14041)   Certificado Tercerizado<br>Country of Origin   Imported       |

WELL V2 Contribution Credit

|  |  |
|--|--|
| X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition                         | <b>Absence of Asbestos</b>                     |
| X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt                   | <b>Absence of Heavy Metals</b>                 |
| X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt | <b>Absence of Halogenated Flame Retardants</b> |
| Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt                               | <b>Ortho-Phthalates</b>                        |
| X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt                                     | <b>FloorScore Certificate</b>                  |

Contribución Para Créditos Leed

|  |  |
|--|--|
| Crédito MR: Divulgación y optimización de productos de construcción<br>Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD) | <b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>  |
| Crédito EQ: Materiales de baja emisión<br>Opción 1: Cálculos de categoría de producto  | <b>FloorScore® Certified</b>   |
| <a href="#">Installation Guidelines</a>  | Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.<br>Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.<br><br>This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.<br><br>Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information. |
| <a href="#">Maintenance Guidelines</a>   |  |

Available Colorways

|   |  |  |   |  |  |
|---|--|--|---|--|--|
|  <div>Golden Cherry 01451<br/>V3 - Moderate Variation<br/>Weldrod 01451</div> |  <div>Indian Cherry 01452<br/>V3 - Moderate Variation<br/>Weldrod 01425</div> |  <div>Noble Zelkova 01811<br/>V3 - Moderate Variation<br/>Weldrod 01811</div> |  <div>Tiger Oak 01821<br/>V3 - Moderate Variation<br/>Weldrod 01821</div> |  <div>Windsor Oak 01822<br/>V3 - Moderate Variation<br/>Weldrod 01452</div> |  <div>Antique Oak 01823<br/>V3 - Moderate Variation<br/>Weldrod 01823</div> |
|  <div>Grand Maple 02001<br/>V3 - Moderate Variation<br/>Weldrod 02001</div>   |  <div>Red 06200<br/>V1 - Uniform Appearance<br/>Weldrod 06200</div>           |  <div>Beige 06301<br/>V1 - Uniform Appearance<br/>Weldrod 06301</div>         |  <div>Gray 06303<br/>V1 - Uniform Appearance<br/>Weldrod 06303</div>      |  <div>Dark Blue 06400<br/>V1 - Uniform Appearance<br/>Weldrod 06400</div>   |  <div>Blue 06402<br/>V1 - Uniform Appearance<br/>Weldrod 06402</div>        |
|  <div>Sky Blue 06403<br/>V1 - Uniform Appearance<br/>Weldrod 06403</div>     |  <div>Yellow 06500<br/>V1 - Uniform Appearance<br/>Weldrod 06500</div>       |  <div>Dark Green 06606<br/>V1 - Uniform Appearance<br/>Weldrod 06606</div>   |  <div>Orange 06901<br/>V1 - Uniform Appearance<br/>Weldrod 06901</div>   |  |  |

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

