

Rexcourt Sheet


Número De Estilo	0004V	
Número De Estilo De Barra De Soldadura	021VS	
Construcción	Manta Vinílica Comercial Heterogénea Con Fibra De Vidrio	
clase		
Clase De Base	Espuma Celular Cerrada	
Terminación	UV Urethane	
	U.s.	Metric
Desgaste De La Capa De Uso	39 mil (0.039 in)	0.99 mm
Espesor Total Del Producto	0.256 in	6.5 mm
Installation Type	Dry Back	
Adhesivo Recomendado	4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Embalaje

Tamaño Real Del Rollo	5.91 ft w x 49.20 ft l	1.80 m w x 15.00 m l
Área Por Rollo	32.22 sy/roll	26.94 sq m/roll
Peso Por Rollo	253.6 lbs	115.03 kg



Método De Instalación Recomendado



desempeño + pruebas

Flexibility (ASTM F137)	Passes
resistencia al calor (ASTM F1514)	Passes
resistencia a la luz (ASTM F1515)	Passes
resistencia a productos químicos (ASTM F925)	Passes
panel radiante (ASTM E648)	Passes, Class I
coeficiente de fricción (ASTM D2407, resistencia al deslizamiento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

10 Años Limitado A Uso Comercial

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificaciones

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.403 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) Certificado Tercerizado Country of Origin Imported

WELL V2 Contribution Credit


X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Contribución Para Créditos Leed


Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	FloorScore® Certified

Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice. This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. Visit shawcontract.com/testing for more information.
Maintenance Guidelines	


Available Colorways




Golden Cherry 01451
V3 - Moderate Variation
Weldrod 01451




Indian Cherry 01452
V3 - Moderate Variation
Weldrod 01425




Noble Zelkova 01811
V3 - Moderate Variation
Weldrod 01811




Tiger Oak 01821
V3 - Moderate Variation
Weldrod 01821



Windsor Oak 01822
V3 - Moderate Variation
Weldrod 01452




Antique Oak 01823
V3 - Moderate Variation
Weldrod 01823



Grand Maple 02001
V3 - Moderate Variation
Weldrod 02001



Red 06200
V1 - Uniform Appearance
Weldrod 06200



Beige 06301
V1 - Uniform Appearance
Weldrod 06301



Gray 06303
V1 - Uniform Appearance
Weldrod 06303



Dark Blue 06400
V1 - Uniform Appearance
Weldrod 06400



Blue 06402
V1 - Uniform Appearance
Weldrod 06402



Sky Blue 06403
V1 - Uniform Appearance
Weldrod 06403



Yellow 06500
V1 - Uniform Appearance
Weldrod 06500



Dark Green 06606
V1 - Uniform Appearance
Weldrod 06606



Orange 06901
V1 - Uniform Appearance
Weldrod 06901

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

