

Rexcourt Sheet


Número De Estilo	0004V	
Número De Estilo De Barra De Soldadura	021VS	
Construcción	Manta Vinílica Comercial Heterogénea Con Fibra De Vidrio	
clase		
Clase De Base	Espuma Celular Cerrada	
Terminación	UV Urethane	
	U.s.	Metric
Desgaste De La Capa De Uso	39 mil (0.039 in)	0.99 mm
Espesor Total Del Producto	0.256 in	6.5 mm
Installation Type	Dry Back	
Adhesivo Recomendado	4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	



Embalaje

Tamaño Real Del Rollo	5.91 ft w x 49.20 ft l	1.80 m w x 15.00 m l
Área Por Rollo	32.22 sy/roll	26.94 sq m/roll
Peso Por Rollo	253.6 lbs	115.03 kg

Método De Instalación Recomendado



desempeño + pruebas

Flexibility (ASTM F137)	Passes
resistencia al calor (ASTM F1514)	Passes
resistencia a la luz (ASTM F1515)	Passes
resistencia a productos químicos (ASTM F925)	Passes
panel radiante (ASTM E648)	Passes, Class I
coeficiente de fricción (ASTM D2407, resistencia al deslizamiento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

10 Años Limitado A Uso Comercial

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Atributos + Certificaciones

Health & Wellbeing	
Indoor Air Quality	FloorScore®   Certificado
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041)   Certificado Tercerizado Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>FloorScore Certificate</b>

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	<b>FloorScore® Certified</b>

<a href="#">Installation Guidelines</a>	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.  Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information.
<a href="#">Maintenance Guidelines</a>	

Available Colorways

 Golden Cherry 01451 V3 - Moderate Variation Weldrod 01451	 Indian Cherry 01452 V3 - Moderate Variation Weldrod 01425	 Noble Zelkova 01811 V3 - Moderate Variation Weldrod 01811	 Tiger Oak 01821 V3 - Moderate Variation Weldrod 01821	 Windsor Oak 01822 V3 - Moderate Variation Weldrod 01452	 Antique Oak 01823 V3 - Moderate Variation Weldrod 01823
 Grand Maple 02001 V3 - Moderate Variation Weldrod 02001	 Red 06200 V1 - Uniform Appearance Weldrod 06200	 Beige 06301 V1 - Uniform Appearance Weldrod 06301	 Gray 06303 V1 - Uniform Appearance Weldrod 06303	 Dark Blue 06400 V1 - Uniform Appearance Weldrod 06400	 Blue 06402 V1 - Uniform Appearance Weldrod 06402
 Sky Blue 06403 V1 - Uniform Appearance Weldrod 06403	 Yellow 06500 V1 - Uniform Appearance Weldrod 06500	 Dark Green 06606 V1 - Uniform Appearance Weldrod 06606	 Orange 06901 V1 - Uniform Appearance Weldrod 06901		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

