

Rexcourt Sheet


Número Do Produto	0004V	
Número Do Estilo Da Haste De Soldagem	021VS	
Construção	Manta Comercial Heterogênea Com Fibra De Vidro	
classe		
Tipo De Base	Espuma de Célula Fechada	
Acabamento	UV Urethane	
	U.s.	Metric
Espessura Da Camada De Uso	39 mil (0.039 in)	0.99 mm
Espessura Total Do Produto	0.256 in	6.5 mm
Installation Type	Dry Back	
Adesivo Recomendado	4200 Resilient Sheet 1 Gallon, 4200 Reslient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	



Empacotamento

Tamanho Real Do Rolo	5.91 ft w x 49.20 ft l	1.80 m w x 15.00 m l
Área Por Rolo	32.22 sy/roll	26.94 sq m/roll
Peso Por Rolo	253.6 lbs	115.03 kg

Método De Instalação Recomendado



Desempenho + Teste

Flexibilidade (Astm F137)	Passes
Resistência Ao Calor (Astm F1514)	Passes
Resistência À Luz (Astm F1515)	Passes
Resistência A Produtos Químicos (Astm F925)	Passes
Painel Radiante (Astm E648)	Passes, Class I
Coefficiente De Atrito (Astm D2407, Resistência Ao Deslizamento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

10 Anos Comercial Limitada

Diversity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw’s diverse customer base and local community. More than 42% of our spend***** is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Atributos + Certificações

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) Certificado 3rd Party
	Country of Origin Imported

WELL V2 Contribution Credit


X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Crédito De Contribuição


MR Credit: Divulgação e otimização de produtos de construção	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	FloorScore® Certified
Crédito de EQ: Materiais de baixa emissão	
Opção 1: cálculos de categoria de produto	

Installation Guidelines	Please visit www.shawcontract.com for the most current warranty information.
Maintenance Guidelines	Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.
	This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
	*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.
	Visit shawcontract.com/testing for more information.


Available Colorways




Golden Cherry 01451
V3 - Moderate Variation
Weldrod 01451




Indian Cherry 01452
V3 - Moderate Variation
Weldrod 01425




Noble Zelkova 01811
V3 - Moderate Variation
Weldrod 01811




Tiger Oak 01821
V3 - Moderate Variation
Weldrod 01821




Windsor Oak 01822
V3 - Moderate Variation
Weldrod 01452



Antique Oak 01823
V3 - Moderate Variation
Weldrod 01823




Grand Maple 02001
V3 - Moderate Variation
Weldrod 02001



Red 06200
V1 - Uniform Appearance
Weldrod 06200



Beige 06301
V1 - Uniform Appearance
Weldrod 06301



Gray 06303
V1 - Uniform Appearance
Weldrod 06303



Dark Blue 06400
V1 - Uniform Appearance
Weldrod 06400



Blue 06402
V1 - Uniform Appearance
Weldrod 06402



Sky Blue 06403
V1 - Uniform Appearance
Weldrod 06403



Yellow 06500
V1 - Uniform Appearance
Weldrod 06500



Dark Green 06606
V1 - Uniform Appearance
Weldrod 06606



Orange 06901
V1 - Uniform Appearance
Weldrod 06901

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

