

Rexcourt Sheet

Número Do Produto	0004V	
Número Do Estilo Da Haste De Soldagem	021VS	
Construção	Manta Comercial Heterogênea Com Fibra De Vidro	
classe		
Tipo De Base	Espuma de Célula Fechada	
Acabamento	UV Urethane	
	U.s.	Metric
Espessura Da Camada De Uso	39 mil (0.039 in)	0.99 mm
Espessura Total Do Produto	0.256 in	6.5 mm
Installation Type	Dry Back	
Adesivo Recomendado	4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, or 4151 Multi-Use Premium 4 Gallon	

Empacotamento

Tamanho Real Do Rolo	5.91 ft w x 49.20 ft l	1.80 m w x 15.00 m l
Área Por Rolo	32.22 sy/roll	26.94 sq m/roll
Peso Por Rolo	253.6 lbs	115.03 kg



Método De Instalação Recomendado



Reverso

desempenho + teste

Flexibility (ASTM F137)	Passes
resistência ao calor (ASTM F1514)	Passes
resistência à luz (ASTM F1515)	Passes
resistência a produtos químicos (ASTM F925)	Passes
painel radiante (ASTM E648)	Passes, Class I
coeficiente de atrito (ASTM D2407, resistência ao deslizamento)	>0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[10 Anos Comercial Limitada](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificações

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.403 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) Certificado 3rd Party Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	FloorScore® Certified
Crédito de EQ: Materiais de baixa emissão	
Opção 1: cálculos de categoria de produto	

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Golden Cherry 01451 V3 - Moderate Variation Weldrod 01451	Indian Cherry 01452 V3 - Moderate Variation Weldrod 01425	Noble Zelkova 01811 V3 - Moderate Variation Weldrod 01811	Tiger Oak 01821 V3 - Moderate Variation Weldrod 01821	Windsor Oak 01822 V3 - Moderate Variation Weldrod 01452	Antique Oak 01823 V3 - Moderate Variation Weldrod 01823
					
Grand Maple 02001 V3 - Moderate Variation Weldrod 02001	Red 06200 V1 - Uniform Appearance Weldrod 06200	Beige 06301 V1 - Uniform Appearance Weldrod 06301	Gray 06303 V1 - Uniform Appearance Weldrod 06303	Dark Blue 06400 V1 - Uniform Appearance Weldrod 06400	Blue 06402 V1 - Uniform Appearance Weldrod 06402
					
Sky Blue 06403 V1 - Uniform Appearance Weldrod 06403	Yellow 06500 V1 - Uniform Appearance Weldrod 06500	Dark Green 06606 V1 - Uniform Appearance Weldrod 06606	Orange 06901 V1 - Uniform Appearance Weldrod 06901		

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

