

Basstones Sheet


Número De Estilo	0301V	
Número De Estilo De Barra De Soldadura	353VS	
Construcción	Manta Vinílica Comercial Heterogénea Con Fibra De Vidrio	
clase	Type I, Grade 1, Class B	
Clase De Base	Sistema de base fusionado de 4 capas	
Terminación	ExoGuard®	
	U.s.	Metric
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.087 in	2.2 mm
Instalación	Direct Glue	
Adhesivo Recomendado	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, or 4151 Multi-Use Premium 4 Gallon	

Embalaje

Tamaño Real Del Rollo	6.00 ft w x 75.00 ft l	1.83 m w x 22.86 m l
Área Por Rollo	50 sy/roll	41.81 sq m/roll
Peso Por Rollo	267.5 lbs	121.34 kg



Método De Instalación Recomendado



desempeño + pruebas

carga estática (ASTM F970)	Passes (Modified), *1500 lbs	*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.
margen adicional residual (ASTM F1914)	Passes	
Flexibility (ASTM F137)	Passes	
resistencia al calor (ASTM F1514)	Passes	
resistencia a la luz (ASTM F1515)	Passes	
resistencia a productos químicos (ASTM F925)	Passes	
densidad de humo (ASTM E662, modo flameado)	Passes	
panel radiante (ASTM E648)	Passes, Class I	
coeficiente de fricción (ASTM D2407, resistencia al deslizamiento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

[15 Años Limitado A Uso Comercial](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificaciones

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.4 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) Certificado Tercerizado
	Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Crédito EQ: Materiales de baja emisión Opción 1: Cálculos de categoría de producto	FloorScore® Certified

[Installation Guidelines](#)

[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

 <div>Flaxen Vibe 00100 Weldrod 02001</div>	 <div>Ecru Cadence 00110 Weldrod 02001</div>	 <div>Desert Sound 00120 Weldrod 02027</div>	 <div>Polished Brass 00140 Weldrod 09633</div>	 <div>Set Off 00200 Weldrod 02002</div>	 <div>Camel Accent 00210 Weldrod 02025</div>
 <div>Coastal Tempo 00300 Weldrod 02003</div>	 <div>Underscore 00310 Weldrod 02004</div>	 <div>Stanza Sage 00320 Weldrod 02005</div>	 <div>Tonal Vine 00330 Weldrod 02003</div>	 <div>Elevate 00340 Weldrod 02006</div>	 <div>Amplitude 00350 Weldrod 02007</div>
 <div>Aqua Tone 00360 Weldrod 02008</div>	 <div>Graytone Fade 00410 Weldrod 02009</div>	 <div>High Fidelity 00420 Weldrod 02010</div>	 <div>Mineral Score 00430 Weldrod 02011</div>	 <div>Pearly Melody 00500 Weldrod 01203</div>	 <div>Pewter Serenade 00530 Weldrod 05244</div>
 <div>Ashen Interval 00540 Weldrod 02014</div>	 <div>Boost 00600 Weldrod 02017</div>	 <div>Adobe Verse 00610 Weldrod 02018</div>	 <div>Chorale Clay 00630 Weldrod 01823</div>	 <div>Khaki Cue 00700 Weldrod 02019</div>	 <div>Neutral Intro 00710 Weldrod 02020</div>
 <div>Gilded Mink 00750 Weldrod 02026</div>	 <div>Coffee Echo 00760 Weldrod 05230</div>	 <div>Amplify 00800 Weldrod 02022</div>	 <div>Emphasize 00900 Weldrod 02024</div>		

