

Basstones Sheet

Número Do Produto	0301V	
Número Do Estilo Da Haste De Soldagem	353VS	
Construção	Manta Comercial Heterogênea Com Fibra De Vidro	
classe	Type I, Grade 1, Class B	
Tipo De Base	Sistema de revestimento fundido de 4 camadas	
Acabamento	ExoGuard®	
	U.s.	Metric
Espessura Da Camada De Uso	20 mil (0.02 in)	0.51 mm
Espessura Total Do Produto	0.087 in	2.2 mm
Instalação	Direct Glue	
Adesivo Recomendado	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon, or 4151 Multi-Use Premium 4 Gallon	

Empacotamento

Tamanho Real Do Rolo	6.00 ft w x 75.00 ft l	1.83 m w x 22.86 m l
Área Por Rolo	50 sy/roll	41.81 sq m/roll
Peso Por Rolo	267.5 lbs	121.34 kg



Método De Instalação Recomendado



Reverso

desempenho + teste

carga estática (ASTM F970)	Passes (Modified), *1500 lbs
recuo residual (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
resistência ao calor (ASTM F1514)	Passes
resistência à luz (ASTM F1515)	Passes
resistência a produtos químicos (ASTM F925)	Passes
densidade de fumaça (ASTM E662, modo flamejante)	Passes
painel radiante (ASTM E648)	Passes, Class I
coeficiente de atrito (ASTM D2407, resistência ao deslizamento)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

[15 Anos Comercial Limitada](#)
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity & Inclusion

We promote supplier participation that is reflective of Shaw Industries' diverse customer base and local community. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

Atributos + Certificações

Health & Wellbeing	
Indoor Air Quality	FloorScore® Certificado
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	9.4 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) Certificado 3rd Party Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)	FloorScore® Certified
Crédito de EQ: Materiais de baixa emissão	
Opção 1: cálculos de categoria de produto	

[Installation Guidelines](#)

Maintenance Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

 <div>Flaxen Vibe 00100 Weldrod 02001</div>	 <div>Ecru Cadence 00110 Weldrod 02001</div>	 <div>Desert Sound 00120 Weldrod 02027</div>	 <div>Polished Brass 00140 Weldrod 09633</div>	 <div>Set Off 00200 Weldrod 02002</div>	 <div>Camel Accent 00210 Weldrod 02025</div>
 <div>Coastal Tempo 00300 Weldrod 02003</div>	 <div>Underscore 00310 Weldrod 02004</div>	 <div>Stanza Sage 00320 Weldrod 02005</div>	 <div>Tonal Vine 00330 Weldrod 02003</div>	 <div>Elevate 00340 Weldrod 02006</div>	 <div>Amplitude 00350 Weldrod 02007</div>
 <div>Aqua Tone 00360 Weldrod 02008</div>	 <div>Graytone Fade 00410 Weldrod 02009</div>	 <div>High Fidelity 00420 Weldrod 02010</div>	 <div>Mineral Score 00430 Weldrod 02011</div>	 <div>Pearly Melody 00500 Weldrod 01203</div>	 <div>Pewter Serenade 00530 Weldrod 05244</div>
 <div>Ashen Interval 00540 Weldrod 02014</div>	 <div>Boost 00600 Weldrod 02017</div>	 <div>Adobe Verse 00610 Weldrod 02018</div>	 <div>Chorale Clay 00630 Weldrod 01823</div>	 <div>Khaki Cue 00700 Weldrod 02019</div>	 <div>Neutral Intro 00710 Weldrod 02020</div>
 <div>Gilded Mink 00750 Weldrod 02026</div>	 <div>Coffee Echo 00760 Weldrod 05230</div>	 <div>Amplify 00800 Weldrod 02022</div>	 <div>Emphasize 00900 Weldrod 02024</div>		

