

Basstones Sheet

Style Number	0301V	
Welding Rod Style Number	353VS	
Construction	Commercial Heterogeneous Sheet With Fiberglass	
Class / ASTM F1303	Type I, Grade 1, Class B	
Backing Class	4-ply Fused Backing System	
Finish	ExoGuard®	
	U.S.	Metric
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.087 in	2.2 mm
Installation	Direct Glue	
Recommended Adhesive	S150-95 Resilient Tile Spray, 4200 Resilient Sheet 1 Gallon, 4200 Resilient Sheet 4 Gallon or 4151 Multi-Use Premium 4 Gallon	

Packaging

Actual Roll Size	6.00 ft w x 75.00 ft l	1.83 m w x 22.86 m l
Area per Roll	50 sy/roll	41.81 sq m/roll
Weight per Roll	267.5 lbs	121.34 kg



Recommended Installation Method



Reverse

Performance + Testing

Static Load (ASTM F970)	Passes (Modified), *1500 lbs
Residual Indentation (ASTM F1914)	Passes
Flexibility (ASTM F137)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Coefficient of Friction (ASTM D2047, Slip Resistance)	≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

\*This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited Warranty](#)  
[Commercial 15 Year Underbed Bond Warranty](#)

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Material Health & Environmental Certifications

Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	FloorScore®   Certified GSA   Approved CE Marking (EN 14041)   3rd Party Certified Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization	Absence of Halogenated Flame Retardants
X10 Volatile Compound Reduction Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization	FloorScore Certificate

Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore Certified

Installation Guidelines	
Maintenance Guidelines	Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited. *****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.  Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information.

Available Colorways

 <div>Flaxen Vibe 00100 Weldrod 02001</div>	 <div>Ecrú Cadence 00110 Weldrod 02001</div>	 <div>Desert Sound 00120 Weldrod 02027</div>	 <div>Polished Brass 00140 Weldrod 09633</div>	 <div>Set Off 00200 Weldrod 02002</div>	 <div>Camel Accent 00210 Weldrod 02025</div>
 <div>Coastal Tempo 00300 Weldrod 02003</div>	 <div>Underscore 00310 Weldrod 02004</div>	 <div>Stanza Sage 00320 Weldrod 02005</div>	 <div>Tonal Vine 00330 Weldrod 02003</div>	 <div>Elevate 00340 Weldrod 02006</div>	 <div>Amplitude 00350 Weldrod 02007</div>
 <div>Aqua Tone 00360 Weldrod 02008</div>	 <div>Graytone Fade 00410 Weldrod 02009</div>	 <div>High Fidelity 00420 Weldrod 02010</div>	 <div>Mineral Score 00430 Weldrod 02011</div>	 <div>Pearly Melody 00500 Weldrod 01203</div>	 <div>Pewter Serenade 00530 Weldrod 05244</div>
 <div>Ashen Interval 00540 Weldrod 02014</div>	 <div>Boost 00600 Weldrod 02017</div>	 <div>Adobe Verse 00610 Weldrod 02018</div>	 <div>Chorale Clay 00630 Weldrod 01823</div>	 <div>Khaki Cue 00700 Weldrod 02001</div>	 <div>Neutral Intro 00710 Weldrod 02020</div>
 <div>Gilded Mink 00750 Weldrod 02026</div>	 <div>Coffee Echo 00760 Weldrod 05230</div>	 <div>Amplify 00800 Weldrod 02022</div>	 <div>Emphasize 00900 Weldrod 02024</div>		

