

Stratum XI

|                           |  |                          |
|---------------------------|--|--------------------------|
| Collection                | Stratum  |                          |
| Style Number              | 034UV  |                          |
| Construction              | Multilayer WPC With Attached Cork Underlayment   |                          |
| class                     | Class III, Type B  |                          |
| Attached Underlayment     | Cork   |                          |
| Finish                    | ExoGuard®  |                          |
|                           | U.s.   | Metric                   |
| Nominal Dimensions        | 9 in w x 72 in l   | 23 cm w x 183 cm l       |
| Actual Dimensions         | 8.98 in w x 72.05 in l   | 22.81 cm w x 183.01 cm l |
| Wear Layer Thickness      | 20 mil (0.02 in)   | 0.51 mm                  |
| Overall Product Thickness | 0.319 in   | 8.1 mm                   |
| Edge Profile              | Micro-Bevel  |                          |
| Installation Type         | Click  |                          |
| Installation              | Floating Or Direct Glue  |                          |
| Recommended Adhesive      | , 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL |                          |

Packaging

|                |             |          |
|----------------|-------------|----------|
| Pieces Per Box | 6 pcs       |          |
| Area Per Box   | 26.95 sq ft | 2.5 sq m |
| Weight Per Box | 47.02 lbs   | 21.33 kg |

Recommended Installation Method



Coordinating Products

COREtec: Stratum 500, Stratum 700, Stratum Eiris, Stratum Linear, Defined, Stratum Nordic

Performance + Testing

|                                     |                 |
|-------------------------------------|-----------------|
| Residual Indentation (Astm F1914)   | Passes          |
| Resistance To Heat (Astm F1514)     | Passes          |
| Resistance To Light (Astm F1515)    | Passes          |
| Resistance To Chemicals (Astm F925) | Passes          |
| Radiant Panel (Astm E648)           | Passes, Class I |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)

Attributes + Certifications

Health & Wellbeing

- Material Ingredient Transparency
- Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
FloorScore® | Certified

Climate Impact

- Environmental Product Declaration (EPD)
- Total Recycled Content

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | China

Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 1: Material Ingredient Reporting

Health Product Declaration (HPD) | 100 Ppm Disclosure

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

FloorScore Certified

[Installation Guidelines](#)  
[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.


Available Colorways



Beacon Hill Oak 00604  
V2 - Slight Variation



Fort Hill Oak 00609  
V4 - Substantial Variation



Newbury Oak 00611  
V2 - Slight Variation



Fenway Oak 00615  
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1



Uniform Appearance

V2



Slight Variation

V3



Moderate Variation

V4



Substantial Variation

