

Stratum XI


コレクション	Stratum
スタイルナンバー	034UV
建設	コルク下敷を含む多層WPC
クラス	Class III, Type B
付属下敷	コルク
仕上げ	ExoGuard®
公称寸法	米国 メートル法
	9 in w x 72 in l 23 cm w x 183 cm l
実際の寸法	8.98 in w x 72.05 in l 22.81 cm w x 183.01 cm l
摩耗層の厚さ	20 mil (0.02 in) 0.51 mm
製品全体の厚さ	0.319 in 8.1 mm
エッジプロファイル	マイクロベベル
Installation Type	Click
インストール	Floating Or Direct Glue
推奨接着剤	, 4200 Resilient Tile 4 Gallon, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail, , 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL



包装

ボックスあたりの個数	6 pcs	
ボックスあたりの面積	26.95 sq ft	2.5 sq m
ボックスあたりの重量	47.02 lbs	21.33 kg

推奨インストール方法



コーディネート商品

COREtec: Stratum 500, Stratum 700, Stratum Eiris, Defined, Stratum Nordic

パフォーマンス + テスト

残留圧痕 (ASTM F1914)	Passes
耐熱性 (ASTM F1514)	Passes
耐光性 (ASTM F1515)	Passes
耐薬品性 (ASTM F925)	Passes
放射パネル (ASTM E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証

属性+認定

Health & Wellbeing

Material Ingredient Transparency
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | 認証取得
Greenguard Gold | 認証取得

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)
Total Recycled Content

ISO 14025、EN 15804 および ISO 21930:2017 に基づく 第三者認証取得
11.2 Kg CO₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

Country of Origin | 中国

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
Greenguard Gold Certificate

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築
材料成分-オプション1：材料成分レポート
MRクレジット：製品の開示と最適化の構築
環境製品宣言-オプション1：環境製品宣言（EPD）
EQクレジット：低排出材料
オプション1：製品カテゴリの計算

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore & Greenguard Gold Certified


[Installation Guidelines](#)
[Maintenance Guidelines](#)

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.


Available Colorways




Beacon Hill Oak 00604
V2 - Slight Variation



Fort Hill Oak 00609
V4 - Substantial Variation



Newbury Oak 00611
V2 - Slight Variation



Fenway Oak 00615
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

