


Stratum XI

|                       |  |                          |
|-----------------------|--|--------------------------|
| Collection            | Stratum  |                          |
| Style Number          | 034UV  |                          |
| Construction          | Multilayer WPC With Attached Cork Underlayment   |                          |
| Class / ASTM F3261    | Class III, Type B  |                          |
| Attached Underlayment | Cork   |                          |
| Finish                | ExoGuard®  |                          |
|                       | U.S.   | Metric                   |
| Nominal Dimensions    | 9 in w x 72 in l   | 23 cm w x 183 cm l       |
| Actual Dimensions     | 8.98 in w x 72.05 in l   | 22.81 cm w x 183.01 cm l |
| Wear Layer Thickness  | 20 mil (0.02 in)   | 0.51 mm                  |
| Overall Thickness     | 0.319 in   | 8.1 mm                   |
| Edge Profile          | Micro-Bevel  |                          |
| Installation Type     | Click  |                          |
| Installation          | Floating Or Direct Glue  |                          |
| Recommended Adhesive  | 4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL |                          |

Packaging

|                   |             |          |
|-------------------|-------------|----------|
| Pieces per Carton | 6 pcs       |          |
| Area per Carton   | 26.95 sq ft | 2.5 sq m |
| Weight per Carton | 47.02 lbs   | 21.33 kg |

Recommended Installation Method



Coordinating Products

None: Stratum 1200  
COREtec: Stratum 500, Stratum 700, Stratum Eiris, Stratum Linear, Defined

Performance + Testing

|                                     |                 |
|-------------------------------------|-----------------|
| Static Load (ASTM F970)             | Passes          |
| Residual Indentation (ASTM F1914)   | Passes          |
| Resistance to Heat (ASTM F1514)     | Passes          |
| Resistance to Light (ASTM F1515)    | Passes          |
| Resistance to Chemicals (ASTM F925) | Passes          |
| Radiant Panel (ASTM E648)           | Passes, Class I |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited Warranty](#)

Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and openingnew markets for growth.

Material Health & Environmental Certifications

|   |   |
|---|---|
| Health & Wellbeing                      |   |
| Material Ingredient Transparency        | <a href="#">Health Product Declaration (HPD)   1000 ppm Disclosure</a>  |
| Climate Impact                          |   |
| Environmental Product Declaration (EPD) | <a href="#">3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</a>                                    |
| Total Recycled Content                  | 0% (Pre-Consumer 0%   Post-Consumer 0%)   |
| Global Product Assessment               | <a href="#">FloorScore®   Certified</a><br>Greenguard (Certification, Gold, Private Label)   Certified<br>Country of Origin   China |

WELL V2 Contribution Credit

|  |  |
|--|--|
| X01 Fundamental Material Precautions<br>Part 1: (C): Restrict Asbestos Precondition                    | <b>Absence of Asbestos</b>                     |
| X08 Hazardous Material Reduction<br>Part 1: Limit Hazardous Materials Optimization                     | <b>Absence of Heavy Metals</b>                 |
| X10 Volatile Compound Reduction<br>Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization   | <b>Absence of Halogenated Flame Retardants</b> |
| X10 Volatile Compound Reduction<br>Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization | <b>Ortho-Phthalates</b>                        |
| X11 Long Term Emissions Control<br>Part 2: Flooring Optimization                                       | <b>Greenguard Gold Certificate</b>             |

Leed v4 Contribution Credits

|   |   |
|---|---|
| MR Credit: Building Product Disclosure and Optimization<br>Material Ingredients - Option 1: Material Ingredient Reporting                         | <b>Health Product Declaration (HPD)   100 Ppm Disclosure</b>                            |
| MR Credit: Building Product Disclosure and Optimization<br>Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD) | <b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b> |
| EQ Credit: Low Emitting Materials<br>Option 1: Product Category Calculations  | <b>FloorScore &amp; Greenguard Gold Certified</b>                                       |

|   |   |
|---|---|
| <a href="#">Installation Guidelines</a> | <p>Please visit <a href="http://www.shawcontract.com">www.shawcontract.com</a> for the most current warranty information.</p> <p>Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.</p> <p>This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.</p> <p>*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.</p> <p>Visit <a href="http://shawcontract.com/testing">shawcontract.com/testing</a> for more information.</p> |
| <a href="#">Maintenance Guidelines</a>  |   |

Available Colorways



Beacon Hill Oak 00604  
V2 - Slight Variation



Fort Hill Oak 00609  
V4 - Substantial Variation




Newbury Oak 00611  
V2 - Slight Variation




Fenway Oak 00615  
V2 - Slight Variation

**Color and Visual Variation Index**


Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1


Uniform Appearance

V2

Slight Variation

V3

Moderate Variation

V4

Substantial Variation

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x 550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +1 800 556 302

© 2024 Shaw Industries Group, Inc., a Berkshire Hathaway Company  
May 3, 2024

3 of 3

For reference purposes only if printed or downloaded.