


Stratum XI

Collection	Stratum	
Numéro De Style	034UV	
Construction	WPC Multicouche Avec Sous-Couche EN Liège Attachée	
classe	Class III, Type B	
Endos Intégrée	Liège	
Finition	ExoGuard®	
Dimensions Nominales	Impérial	Métrique
	9 in w x 72 in l	23 cm w x 183 cm l
	8.98 in w x 72.05 in l	22.81 cm w x 183.01 cm l
	20 mil (0.02 in)	0.51 mm
	0.319 in	8.1 mm
	Micro-Biseau	
	Click	
Installation Type	Floating Or Direct Glue	
Installation	4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	
Adhésif Recommandé		

Emballage

Pièces Par Carton	6 pcs	
Surface Par Carton	26.95 sq ft	2.5 sq m
Poids Par Carton	47.02 lbs	21.33 kg

Méthodes d'Installation Conseillées



Coordination Des Produits

None: Stratum 1200  
COREtec: Stratum 500, Stratum 700, Stratum Eiris, Stratum Linear, Defined

Performance + Tests Et Essai

Poinçonnement Rémanent (Astm F1914)	Passes
Résistance À La Chaleur (Astm F1514)	Passes
Résistance À La Lumière (Astm F1515)	Passes
Résistance Chimique (Astm F925)	Passes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)

Attributs + Certifications

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025, EN 15804 Et ISO 21930:2017

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Agréé

Greenguard (Certification, Gold, Private Label) | Agréé

Country of Origin | Imported

Contribution Au Certificat Vert Leed

« Crédit MR : Divulcation et optimisation des produits de construction

« Crédit MR : Divulcation et optimisation des produits de construction

Crédit EQ : matériaux faibles émissions

[Installation Guidelines](#)

[Maintenance Guidelines](#)

**Health Product Declaration (HPD) | 100 Ppm Disclosure**  
**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**

**FloorScore & Greenguard Gold Certified**

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
\*\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.


Available Colorways



Beacon Hill Oak 00604  
V2 - Slight Variation



Fort Hill Oak 00609  
V4 - Substantial Variation



Newbury Oak 00611  
V2 - Slight Variation



Fenway Oak 00615  
V2 - Slight Variation

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.



