


Stratum XI

コレクション	Stratum	
スタイルナンバー	034UV	
建設	コルク下敷を含む多層WPC	
クラス	Class III, Type B	
付属下敷	コルク	
仕上げ	ExoGuard®	
公称寸法	9 in w x 72 in l	メートル法
実際の寸法	8.98 in w x 72.05 in l	23 cm w x 183 cm l
摩耗層の厚さ	20 mil (0.02 in)	22.81 cm w x 183.01 cm l
製品全体の厚さ	0.319 in	0.51 mm
エッジプロファイル	マイクロベベル	8.1 mm
Installation Type	Click	
インストール	Floating Or Direct Glue	
推奨接着剤	4200 Resilient Tile 4 Gallon, 2200 Resilient Tile 4 Gallon, 4151 Multi-Use Premium 4 Gallon or SHAW 4100 4 GAL	

包装

ボックスあたりの個数	6 pcs	
ボックスあたりの面積	26.95 sq ft	2.5 sq m
ボックスあたりの重量	47.02 lbs	21.33 kg

推奨インストール方法



コーディネート商品

COREtec: Stratum 500, Stratum 700, Stratum Eiris, Stratum Linear, Defined, Stratum Nordic

パフォーマンス + テスト

残留圧痕 (astm F1914)	Passes
耐熱性 (astm F1514)	Passes
耐光性 (astm F1515)	Passes
耐薬品性 (astm F925)	Passes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

保証

15年の商用限定保証

属性+認定

Health & Wellbeing	Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Climate Impact	Environmental Product Declaration (EPD)	ISO 14025、EN 15804 および ISO 21930:2017 に基づく第三者認証取得
	Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment		FloorScore®   認証取得
		Greenguard (Certification, Gold, Private Label)   認証取得
		Country of Origin   中国

グリーンリード貢献クレジット

MRクレジット：製品の開示と最適化の構築  
材料成分-オプション1：材料成分レポート  
MRクレジット：製品の開示と最適化の構築  
環境製品宣言-オプション1：環境製品宣言 (EPD)  
EQクレジット：低排出材料  
オプション1：製品カテゴリの計算

[Installation Guidelines](#)  
[Maintenance Guidelines](#)

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017


FloorScore & Greenguard Gold Certified

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.


This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways



Beacon Hill Oak 00604  
V2 - Slight Variation



Fort Hill Oak 00609  
V4 - Substantial Variation



Newbury Oak 00611  
V2 - Slight Variation




Fenway Oak 00615  
V2 - Slight Variation

Color and Visual Variation Index


Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1




Uniform Appearance

V2




Slight Variation

V3



Moderate Variation

V4



Substantial Variation

