

Pigment Floating

Collection	Grain + Pigment	
Style Number	0365V	
Construction	Heavy Comm Luxury Vinyl Tile W/ In*step Backing	
class	Class III, Type B	
Finish	ExoGuard®	
	U.s.	Metric
Nominal Dimensions	7 in w x 48 in l	18 cm w x 121 cm l
Actual Dimensions	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Product Thickness	0.157 in	4 mm
Edge Profile	Micro-Bevel	
Installation Type	InStep Locking System	
Installation	Floating	
Recommended Adhesive	, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or	
Packaging		

Pieces Per Box	10 pcs	
Area Per Box	24.13 sq ft	2.24 sq m
Weight Per Box	33.72 lbs	15.3 kg



Recommended Installation Method



Stagger

Coordinating Products

LVT: Grain Floating, Grain Direct Glue, Pigment Direct Glue

performance + testing

residual indentation (ASTM F1914)	Passes
resistance to heat (ASTM F1514)	Passes
resistance to light (ASTM F1515)	Passes
resistance to chemicals (ASTM F925)	Passes
radiant panel (ASTM E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)

Attributes + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD) 1000 ppm Disclosure
Indoor Air Quality	FloorScore® Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Embodied Carbon (Cradle to Gate)	11.59 Kg Co ₂ /M ²
Total Recycled Content	0% (Pre-Consumer 0% Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041) 3rd Party Certified
	Country of Origin Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	Absence of Asbestos
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	Absence of Heavy Metals
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	Absence of Halogenated Flame Retardants
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	Ortho-Phthalates
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	FloorScore Certificate

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	Health Product Declaration (HPD) 100 Ppm Disclosure
MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	FloorScore® Certified













Installation Guidelines

Please visit www.shawcontract.com for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

 <div>Beige 65114 LRV 51.2 L* 76.79 V1 - Uniform Appearance</div>	 <div>Stone 65115 LRV 26.7 L* 58.65 V1 - Uniform Appearance</div>	 <div>Yellow 65201 LRV 42.6 L* 71.29 V1 - Uniform Appearance</div>	 <div>Green 65326 LRV 23.2 L* 55.29 V1 - Uniform Appearance</div>	 <div>Blue 65429 LRV 9.8 L* 37.4 V1 - Uniform Appearance</div>	 <div>Cyan 65436 LRV 18.7 L* 50.33 V1 - Uniform Appearance</div>
 <div>Bone 65515 LRV 54.8 L* 78.91 V1 - Uniform Appearance</div>	 <div>Grey 65530 LRV 26.2 L* 58.19 V1 - Uniform Appearance</div>	 <div>Charcoal 65595 LRV 12.1 L* 41.32 V1 - Uniform Appearance</div>	 <div>Orange 65675 LRV 19.9 L* 51.78 V1 - Uniform Appearance</div>	 <div>Taupe 65761 LRV 13.4 L* 43.29 V1 - Uniform Appearance</div>	 <div>Red 65855 LRV 11.1 L* 39.72 V1 - Uniform Appearance</div>

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

