

Pigment Floating

Collection	<b>Grain + Pigment</b>	
Style Number	<b>0365V</b>	
Construction	<b>Heavy Comm Luxury Vinyl Tile W/ In*step Backing</b>	
class	<b>Class III, Type B</b>	
Finish	<b>ExoGuard®</b>	
	U.s.	Metric
Nominal Dimensions	<b>7 in w x 48 in l</b>	<b>18 cm w x 121 cm l</b>
Actual Dimensions	<b>7.28 in w x 47.72 in l</b>	<b>18.49 cm w x 121.21 cm l</b>
Wear Layer Thickness	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Overall Product Thickness	<b>0.157 in</b>	<b>4 mm</b>
Edge Profile	<b>Micro-Bevel</b>	
Installation Type	<b>InStep Locking System</b>	
Installation	<b>Floating</b>	
Recommended Adhesive	<b>, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or</b>	
Packaging		

Pieces Per Box	<b>10 pcs</b>	
Area Per Box	<b>24.13 sq ft</b>	<b>2.24 sq m</b>
Weight Per Box	<b>33.72 lbs</b>	<b>15.3 kg</b>



Recommended Installation Method



Stagger

Coordinating Products

LVT: Grain Floating, Grain Direct Glue, Pigment Direct Glue

performance + testing

residual indentation (ASTM F1914)	<b>Passes</b>
resistance to heat (ASTM F1514)	<b>Passes</b>
resistance to light (ASTM F1515)	<b>Passes</b>
resistance to chemicals (ASTM F925)	<b>Passes</b>
radiant panel (ASTM E648)	<b>Passes, Class I</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

[15 Year Commercial Limited](#)

Attributes + Certifications

Health & Wellbeing	
Material Ingredient Transparency	Health Product Declaration (HPD)   1000 ppm Disclosure
Indoor Air Quality	FloorScore®   Certified
Climate Impact	
Environmental Product Declaration (EPD)	3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
Total Recycled Content	0% (Pre-Consumer 0%   Post-Consumer 0%)
Global Product Assessment	CE Marking (EN 14041)   3rd Party Certified
	Country of Origin   Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition	<b>Absence of Asbestos</b>
X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt	<b>Absence of Heavy Metals</b>
X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt	<b>Absence of Halogenated Flame Retardants</b>
Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt	<b>Ortho-Phthalates</b>
X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt	<b>FloorScore Certificate</b>

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization Material Ingredients - Option 1: Material Ingredient Reporting	<b>Health Product Declaration (HPD)   100 Ppm Disclosure</b>
MR Credit: Building Product Disclosure and Optimization Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)	<b>3rd Party Certified in Accordance with ISO 14025, EN 15804, &amp; ISO 21930:2017</b>
EQ Credit: Low Emitting Materials Option 1: Product Category Calculations	<b>FloorScore® Certified</b>













Installation Guidelines

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

### Available Colorways

					
Beige 65114 LRV 51.2   L* 76.79 V1 - Uniform Appearance	Stone 65115 LRV 26.7   L* 58.65 V1 - Uniform Appearance	Yellow 65201 LRV 42.6   L* 71.29 V1 - Uniform Appearance	Green 65326 LRV 23.2   L* 55.29 V1 - Uniform Appearance	Blue 65429 LRV 9.8   L* 37.4 V1 - Uniform Appearance	Cyan 65436 LRV 18.7   L* 50.33 V1 - Uniform Appearance
					
Bone 65515 LRV 54.8   L* 78.91 V1 - Uniform Appearance	Grey 65530 LRV 26.2   L* 58.19 V1 - Uniform Appearance	Charcoal 65595 LRV 12.1   L* 41.32 V1 - Uniform Appearance	Orange 65675 LRV 19.9   L* 51.78 V1 - Uniform Appearance	Taupe 65761 LRV 13.4   L* 43.29 V1 - Uniform Appearance	Red 65855 LRV 11.1   L* 39.72 V1 - Uniform Appearance

### Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1 	V2 	V3 	V4 
Uniform Appearance	Slight Variation	Moderate Variation	Substantial Variation

