

Pigment Floating

Colección	Grain + Pigment	
Número De Estilo	0365V	
Construcción	Lvt Comercial De Tráfico Severo Con Sistema De Base In*step	
clase	Class III, Type B	
Terminación	ExoGuard®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 48 in l	18 cm w x 121 cm l
Dimensiones Reales	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.157 in	4 mm
Perfil De Borde	Micro-Biselado	
Installation Type	InStep Locking System	
Instalación	Floating	
Adhesivo Recomendado	, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or	

Embalaje

Piezas Por Caja	10 pcs	
Área Por Caja	24.13 sq ft	2.24 sq m
Peso Por Caja	33.72 lbs	15.3 kg



Método De Instalación Recomendado



Stagger

Productos Que Combinan

LVT: Grain Floating, Grain Direct Glue, Pigment Direct Glue

desempeño + pruebas

margen adicional residual (ASTM F1914)	Passes
resistencia al calor (ASTM F1514)	Passes
resistencia a la luz (ASTM F1515)	Passes
resistencia a productos químicos (ASTM F925)	Passes
panel radiante (ASTM E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

15 Años Limitado A Uso Comercial

Atributos + Certificaciones

Health & Wellbeing

- Material Ingredient Transparency
- Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certificado

Climate Impact

- Environmental Product Declaration (EPD)
- Embodied Carbon (Cradle to Gate)
- Total Recycled Content

Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017
11.59 Kg Co₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | Certificado Tercerizado
Country of Origin | Imported

WELL V2 Contribution Credit

- X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
- X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
- X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
- Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
- X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
FloorScore Certificate

Contribución Para Créditos Leed

- Crédito MR: Divulgación y optimización de productos de construcción
Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales
- Crédito MR: Divulgación y optimización de productos de construcción
Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)
- Crédito EQ: Materiales de baja emisión
Opción 1: Cálculos de categoría de producto

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore® Certified













Installation Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Beige 65114 LRV 51.2 L* 76.79 V1 - Uniform Appearance	Stone 65115 LRV 26.7 L* 58.65 V1 - Uniform Appearance	Yellow 65201 LRV 42.6 L* 71.29 V1 - Uniform Appearance	Green 65326 LRV 23.2 L* 55.29 V1 - Uniform Appearance	Blue 65429 LRV 9.8 L* 37.4 V1 - Uniform Appearance	Cyan 65436 LRV 18.7 L* 50.33 V1 - Uniform Appearance
					
Bone 65515 LRV 54.8 L* 78.91 V1 - Uniform Appearance	Grey 65530 LRV 26.2 L* 58.19 V1 - Uniform Appearance	Charcoal 65595 LRV 12.1 L* 41.32 V1 - Uniform Appearance	Orange 65675 LRV 19.9 L* 51.78 V1 - Uniform Appearance	Taupe 65761 LRV 13.4 L* 43.29 V1 - Uniform Appearance	Red 65855 LRV 11.1 L* 39.72 V1 - Uniform Appearance

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1 	V2 	V3 	V4 
Uniform Appearance	Slight Variation	Moderate Variation	Substantial Variation

