

Pigment Floating

Colección	Grain + Pigment	
Número De Estilo	0365V	
Construcción	Lvt Comercial De Tráfico Severo Con Sistema De Base In*step	
clase	Class III, Type B	
Terminación	ExoGuard®	
	U.s.	Metric
Dimensiones Nominales	7 in w x 48 in l	18 cm w x 121 cm l
Dimensiones Reales	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Desgaste De La Capa De Uso	20 mil (0.02 in)	0.51 mm
Espesor Total Del Producto	0.157 in	4 mm
Perfil De Borde	Micro-Biselado	
Installation Type	InStep Locking System	
Instalación	Floating	
Adhesivo Recomendado	, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or	

Embalaje

Piezas Por Caja	10 pcs	
Área Por Caja	24.13 sq ft	2.24 sq m
Peso Por Caja	33.72 lbs	15.3 kg



Método De Instalación Recomendado



Stagger

Productos Que Combinan

LVT: Grain Floating, Grain Direct Glue, Pigment Direct Glue

Desempeño + Pruebas

Margen Adicional Residual (Astm F1914)	Passes
Resistencia Al Calor (Astm F1514)	Passes
Resistencia A La Luz (Astm F1515)	Passes
Resistencia A Productos Químicos (Astm F925)	Passes
Panel Radiante (Astm E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantías

15 Años Limitado A Uso Comercial

Atributos + Certificaciones

Health & Wellbeing

Material Ingredient Transparency  
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
FloorScore® | Certificado

Climate Impact

Environmental Product Declaration (EPD)  
  
Embodied Carbon (Cradle to Gate)  
Total Recycled Content

Certificado Tercerizado De Acuerdo Con La Norma ISO 14025, EN 15804, & ISO 21930:2017  
7.31 Kg Co<sub>2</sub>/M<sup>2</sup>  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | Certificado Tercerizado  
Country of Origin | Imported

Contribución Para Créditos Leed

Crédito MR: Divulgación y optimización de productos de construcción  
Ingredientes de materiales - Opción 1: Informe de ingredientes de los materiales

Crédito MR: Divulgación y optimización de productos de construcción  
Declaraciones ambientales de productos - Opción 1: Declaración ambiental de productos (EPD)

Crédito EQ: Materiales de baja emisión  
Opción 1: Cálculos de categoría de producto

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

Installation Guidelines  
Maintenance







Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.





This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Beige 65114	Stone 65115	Yellow 65201	Green 65326	Blue 65429	Cyan 65436
LRV 51.2   L* 76.79	LRV 26.7   L* 58.65	LRV 42.6   L* 71.29	LRV 23.2   L* 55.29	LRV 9.8   L* 37.4	LRV 18.7   L* 50.33
V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance

					
Bone 65515	Grey 65530	Charcoal 65595	Orange 65675	Taupe 65761	Red 65855
LRV 54.8   L* 78.91	LRV 26.2   L* 58.19	LRV 12.1   L* 41.32	LRV 19.9   L* 51.78	LRV 13.4   L* 43.29	LRV 11.1   L* 39.72
V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

