

Pigment Floating

Collection	<b>Grain + Pigment</b>	
Numéro De Style	<b>0365V</b>	
Construction	<b>Carreau De Vinyle De Luxe Heavy Comm Avec Support In*step</b>	
classe	<b>Class III, Type B</b>	
Finition	<b>ExoGuard®</b>	
	Impérial	Métrique
Dimensions Nominales	<b>7 in w x 48 in l</b>	<b>18 cm w x 121 cm l</b>
Dimensions Réelles	<b>7.28 in w x 47.72 in l</b>	<b>18.49 cm w x 121.21 cm l</b>
Épaisseur De La Couche d'Usure	<b>20 mil (0.02 in)</b>	<b>0.51 mm</b>
Épaisseur Générale Du Produit	<b>0.157 in</b>	<b>4 mm</b>
Profil Du Bord	<b>Micro-Biseau</b>	
Installation Type	<b>InStep Locking System</b>	
Installation	<b>Floating</b>	
Adhésif Recommandé	<b>2200 Semi-Wet Resilient 4 Gallon Pail or 2200 Semi-Wet Resilient 1 Gallon Pail</b>	

Emballage

Pièces Par Carton	<b>10 pcs</b>	
Surface Par Carton	<b>24.13 sq ft</b>	<b>2.24 sq m</b>
Poids Par Carton	<b>33.72 lbs</b>	<b>15.3 kg</b>



Méthodes d'Installation Conseillées



For accent only applications.

Stagger

Coordination Des Produits

LVT: Grain Floating, Grain Direct Glue, Pigment Direct Glue

performance + Tests et essai

poinçonnement rémanent (ASTM F1914)	<b>Passes</b>
résistance à la chaleur (ASTM F1514)	<b>Passes</b>
résistance à la lumière (ASTM F1515)	<b>Passes</b>
résistance chimique (ASTM F925)	<b>Passes</b>
Essai au panneau radiant (Astm E648)	<b>Passes, Class I</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garanties

[Limitée Commerciale De 15 Ans](#)

Attributs + Certifications

Health & Wellbeing

Material Ingredient Transparency  
Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure  
FloorScore® | Agréé

Climate Impact

Environmental Product Declaration (EPD)  
  
Embodied Carbon (Cradle to Gate)  
Total Recycled Content

Certifié Par Une Tierce Partie Conformément Aux Normes ISO 14025,  
EN 15804 Et ISO 21930:2017  
  
11.59 Kg Co<sub>2</sub>/M²  
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | Certifié Par Un Tiers  
Country of Origin | Imported

WELL V2 Contribution Credit

X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition  
X08 Réduction des matières dangereuses Partie 1 : Optimisation des limites des matières dangereuses – 1 pt  
X10 Réduction des composés volatils Partie 1 (A) : Gérer l'optimisation des composés organiques volatils (COV) - 1 pt  
Partie 2 : Gérer l'optimisation des composés organiques semi-volatils (COSV) - 1 pt  
X11 Contrôle des émissions à long terme Partie 2 : Optimisation des revêtements de sol – 1 pt

**Absence of Asbestos**  
**Absence of Heavy Metals**  
  
**Absence of Halogenated Flame Retardants**  
  
**Ortho-Phthalates**  
**FloorScore Certificate**

Contribution Au Certificat Vert Leed













« Crédit MR : Divulgation et optimisation des produits de construction  
« Crédit MR : Divulgation et optimisation des produits de construction  
  
Crédit EQ : matériaux faibles émissions

**Health Product Declaration (HPD) | 100 Ppm Disclosure**  
**3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017**  
**FloorScore Certified**

[Installation Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.  
  
This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.  
  
Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

 <div>Beige 65114 LRV 51.2   L* 76.79 V1 - Uniform Appearance</div>	 <div>Stone 65115 LRV 26.7   L* 58.65 V1 - Uniform Appearance</div>	 <div>Yellow 65201 LRV 42.6   L* 71.29 V1 - Uniform Appearance</div>	 <div>Green 65326 LRV 23.2   L* 55.29 V1 - Uniform Appearance</div>	 <div>Blue 65429 LRV 9.8   L* 37.4 V1 - Uniform Appearance</div>	 <div>Cyan 65436 LRV 18.7   L* 50.33 V1 - Uniform Appearance</div>
 <div>Bone 65515 LRV 54.8   L* 78.91 V1 - Uniform Appearance</div>	 <div>Grey 65530 LRV 26.2   L* 58.19 V1 - Uniform Appearance</div>	 <div>Charcoal 65595 LRV 12.1   L* 41.32 V1 - Uniform Appearance</div>	 <div>Orange 65675 LRV 19.9   L* 51.78 V1 - Uniform Appearance</div>	 <div>Taupe 65761 LRV 13.4   L* 43.29 V1 - Uniform Appearance</div>	 <div>Red 65855 LRV 11.1   L* 39.72 V1 - Uniform Appearance</div>

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

