

Pigment Floating

| | | |
|----------------------------|--|---------------------------------|
| Coleção | Grain + Pigment | |
| Número Do Produto | 0365V | |
| Construção | Vinílico Lvt De Uso Comercial, Tráfego Pesado, Com Base In*step | |
| classe | Class III, Type B | |
| Acabamento | ExoGuard® | |
| | U.s. | Metric |
| Dimensões Nominais | 7 in w x 48 in l | 18 cm w x 121 cm l |
| Dimensões Reais | 7.28 in w x 47.72 in l | 18.49 cm w x 121.21 cm l |
| Espessura Da Camada De Uso | 20 mil (0.02 in) | 0.51 mm |
| Espessura Total Do Produto | 0.157 in | 4 mm |
| Perfil De Borda | Micro-Chanfrado | |
| Installation Type | InStep Locking System | |
| Instalação | Floating | |
| Adesivo Recomendado | , 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or | |

Empacotamento

| | | |
|-----------------|--------------------|------------------|
| Peças Por Caixa | 10 pcs | |
| Área Por Caixa | 24.13 sq ft | 2.24 sq m |
| Peso Por Caixa | 33.72 lbs | 15.3 kg |



Método De Instalação Recomendado



Stagger

Produtos Coordenados

LVT: Grain Floating, Grain Direct Glue, Pigment Direct Glue

desempenho + teste

| | |
|---|------------------------|
| recuo residual (ASTM F1914) | Passes |
| resistência ao calor (ASTM F1514) | Passes |
| resistência à luz (ASTM F1515) | Passes |
| resistência a produtos químicos (ASTM F925) | Passes |
| painel radiante (ASTM E648) | Passes, Class I |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

15 Anos Comercial Limitada

Atributos + Certificações

Health & Wellbeing

- Material Ingredient Transparency
- Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certificado

Climate Impact

- Environmental Product Declaration (EPD)
- Embodied Carbon (Cradle to Gate)
- Total Recycled Content

3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
11.59 Kg Co₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | Certificado 3rd Party
Country of Origin | Imported

WELL V2 Contribution Credit

- X01 Fundamental Material Precautions Part 1: (C): Restrict Asbestos Precondition
- X08 Hazardous Material Reduction Part 1: Limit Hazardous Materials Optimization – 1 pt
- X10 Volatile Compound Reduction Part 1 (A): Manage Volatile Organic Compounds (VOCs) Optimization – 1 pt
- Part 2: Manage Semi-Volatile Organic Compounds (SVOCs) Optimization – 1 pt
- X11 Long Term Emissions Control Part 2: Flooring Optimization – 1 pt

Absence of Asbestos
Absence of Heavy Metals
Absence of Halogenated Flame Retardants

Ortho-Phthalates
FloorScore Certificate

Crédito De Contribuição

- MR Credit: Divulgação e otimização de produtos de construção
Ingredientes materiais - Opção 1: Relatório de ingredientes materiais
- MR Credit: Divulgação e otimização de produtos de construção
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)
- Crédito de EQ: Materiais de baixa emissão
Opção 1: cálculos de categoria de produto

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017
FloorScore® Certified













Installation Guidelines

Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.





Visit shawcontract.com/testing for more information.

Available Colorways

| | | | | | |
|--|---|---|--|---|---|
|  |  |  |  |  |  |
| Beige 65114 LRV 51.2 L* 76.79 V1 - Uniform Appearance | Stone 65115 LRV 26.7 L* 58.65 V1 - Uniform Appearance | Yellow 65201 LRV 42.6 L* 71.29 V1 - Uniform Appearance | Green 65326 LRV 23.2 L* 55.29 V1 - Uniform Appearance | Blue 65429 LRV 9.8 L* 37.4 V1 - Uniform Appearance | Cyan 65436 LRV 18.7 L* 50.33 V1 - Uniform Appearance |
|  |  |  |  |  |  |
| Bone 65515 LRV 54.8 L* 78.91 V1 - Uniform Appearance | Grey 65530 LRV 26.2 L* 58.19 V1 - Uniform Appearance | Charcoal 65595 LRV 12.1 L* 41.32 V1 - Uniform Appearance | Orange 65675 LRV 19.9 L* 51.78 V1 - Uniform Appearance | Taupe 65761 LRV 13.4 L* 43.29 V1 - Uniform Appearance | Red 65855 LRV 11.1 L* 39.72 V1 - Uniform Appearance |

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

| | | | |
|---|--|---|---|
| V1  | V2  | V3  | V4  |
| Uniform Appearance | Slight Variation | Moderate Variation | Substantial Variation |

