

Pigment Floating

Coleção	Grain + Pigment	
Número Do Produto	0365V	
Construção	Vinílico Lvt De Uso Comercial, Tráfego Pesado, Com Base In*step	
classe	Class III, Type B	
Acabamento	ExoGuard®	
	U.s.	Metric
Dimensões Nominais	7 in w x 48 in l	18 cm w x 121 cm l
Dimensões Reais	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Espessura Da Camada De Uso	20 mil (0.02 in)	0.51 mm
Espessura Total Do Produto	0.157 in	4 mm
Perfil De Borda	Micro-Chanfrado	
Installation Type	InStep Locking System	
Instalação	Floating	
Adesivo Recomendado	, 2200 Semi-Wet Resilient 4 Gallon Pail, 2200 Semi-Wet Resilient 1 Gallon Pail or	

Empacotamento

Peças Por Caixa	10 pcs	
Área Por Caixa	24.13 sq ft	2.24 sq m
Peso Por Caixa	33.72 lbs	15.3 kg



Método De Instalação Recomendado



Stagger

Produtos Coordenados

LVT: Grain Floating, Grain Direct Glue, Pigment Direct Glue

Desempenho + Teste

Recuo Residual (Astm F1914)	Passes
Resistência Ao Calor (Astm F1514)	Passes
Resistência À Luz (Astm F1515)	Passes
Resistência A Produtos Químicos (Astm F925)	Passes
Painel Radiante (Astm E648)	Passes, Class I

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Garantias

15 Anos Comercial Limitada

Atributos + Certificações

Health & Wellbeing

- Material Ingredient Transparency
- Indoor Air Quality

Health Product Declaration (HPD) | 1000 ppm Disclosure
FloorScore® | Certificado

Climate Impact

- Environmental Product Declaration (EPD)
- Embodied Carbon (Cradle to Gate)
- Total Recycled Content

3rd Party Certified De Acordo Com ISO 14025, EN 15804, & ISO 21930:2017
7.31 Kg CO₂/M²
0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

CE Marking (EN 14041) | Certificado 3rd Party
Country of Origin | Imported

Crédito De Contribuição

MR Credit: Divulgação e otimização de produtos de construção
Ingredientes materiais - Opção 1: Relatório de ingredientes materiais

Health Product Declaration (HPD) | 100 Ppm Disclosure

MR Credit: Divulgação e otimização de produtos de construção
Declarações ambientais do produto - Opção 1: Declaração ambiental do produto (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

Crédito de EQ: Materiais de baixa emissão
Opção 1: cálculos de categoria de produto

FloorScore Certified







Installation Guidelines
Maintenance







Please visit www.shawcontract.com for the most current warranty information.
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.
*****Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit shawcontract.com/testing for more information.

Available Colorways

					
Beige 65114	Stone 65115	Yellow 65201	Green 65326	Blue 65429	Cyan 65436
LRV 51.2 L* 76.79	LRV 26.7 L* 58.65	LRV 42.6 L* 71.29	LRV 23.2 L* 55.29	LRV 9.8 L* 37.4	LRV 18.7 L* 50.33
V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance

					
Bone 65515	Grey 65530	Charcoal 65595	Orange 65675	Taupe 65761	Red 65855
LRV 54.8 L* 78.91	LRV 26.2 L* 58.19	LRV 12.1 L* 41.32	LRV 19.9 L* 51.78	LRV 13.4 L* 43.29	LRV 11.1 L* 39.72
V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

