

Pigment Floating

Collection	Grain + Pigment	
Style Number	0365V	
Construction	Heavy Comm Luxury Vinyl Tile W/ In*step Backing	
Class / ASTM F1700	Class III, Type B	
Finish	ExoGuard®	
	U.s.	Metric
Nominal Dimensions	7 in w x 48 in l	18 cm w x 121 cm l
Actual Dimensions	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
Wear Layer Thickness	20 mil (0.02 in)	0.51 mm
Overall Thickness	0.157 in	4 mm
Edge Profile	Micro-Bevel	
Installation Type	InStep Locking System	
Installation	Floating	
Recommended Adhesive	2200 Resilient Tile 4 Gallon	

Packaging

Pieces Per Carton	10 pcs	
Area Per Carton	24.13 sq ft	2.24 sq m
Weight Per Carton	33.72 lbs	15.3 kg



Recommended Installation Method



Stagger

Coordinating Products

LVT: Grain Floating, Grain Direct Glue, Pigment Direct Glue

Performance + Testing

Residual Indentation (Astm F1914)	Passes
Resistance To Heat (Astm F1514)	Passes
Resistance To Light (Astm F1515)	Passes
Resistance To Chemicals (Astm F925)	Passes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

15 Year Commercial Limited

Material Health & Environmental Certifications

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

Embodied Carbon (Cradle to Gate)

7.31 Kg Co<sub>2</sub>/M<sup>2</sup>

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | Certified

CE Marking (EN 14041) | 3rd Party Certified

Country of Origin | Imported

Green Leed Contribution Credit

MR Credit: Building Product Disclosure and Optimization  
Material Ingredients - Option 1: Material Ingredient Reporting

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017

FloorScore Certified

Installation Guidelines







Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.







Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Beige 65114	Stone 65115	Yellow 65201	Green 65326	Blue 65429	Cyan 65436
LRV 51.2	LRV 26.7	LRV 42.6	LRV 23.2	LRV 9.8	LRV 18.7
V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance

					
Bone 65515 LRV 54.8	Grey 65530 LRV 26.2	Charcoal 65595 LRV 12.1	Orange 65675 LRV 19.9	Taupe 65761 LRV 13.4	Red 65855 LRV 11.1
V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance	V1 - Uniform Appearance

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

V1 	V2 	V3 	V4 
Uniform Appearance	Slight Variation	Moderate Variation	Substantial Variation

