

Pigment Floating

수집	Grain + Pigment	
스타일 번호	0365V	
구성	"In*step"역행을 가진 헤비급 상업적인 고급 비닐 도와	
수업	Class III, Type B	
끝	ExoGuard®	
	미국	미터법
공칭 치수	7 in w x 48 in l	18 cm w x 121 cm l
실제 치수	7.28 in w x 47.72 in l	18.49 cm w x 121.21 cm l
마모 층 두께	20 mil (0.02 in)	0.51 mm
전체 제품 두께	0.157 in	4 mm
가장자리 프로필	마이크로 베벨	
Installation Type	InStep Locking System	
설치	Floating	
권장 접착제	2200 Resilient Tile 4 Gallon	

포장

상자 당 조각	10 pcs	
상자 당 면적	24.13 sq ft	2.24 sq m
상자 당 무게	33.72 lbs	15.3 kg



권장 설치 방법



Stagger

코디네이팅 제품

LVT: Grain Floating, Grain Direct Glue, Pigment Direct Glue

공연 + 테스트

잔차 들어 쓰기 (Astm F1914)	Passes
내열성 (Astm F1514)	Passes
내광성 (Astm F1515)	Passes
화학 물질에 대한 내성 (Astm F925)	Passes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

보증

15년 상용 제한

속성 + 인증

Health & Wellbeing

Material Ingredient Transparency

Health Product Declaration (HPD) | 1000 ppm Disclosure

Climate Impact

Environmental Product Declaration (EPD)

Embodied Carbon (Cradle to Gate)

Total Recycled Content

ISO 14025, EN 15804 및 ISO 21930:2017에 따라 타사 인증 획득

7.31 Kg Co<sub>2</sub>/M<sup>2</sup>

0% (Pre-Consumer 0% | Post-Consumer 0%)

Global Product Assessment

FloorScore® | 인증

CE Marking (EN 14041) | 타사 인증 획득

Country of Origin | Imported

녹색의 공헌 기여 크레딧

MR 크레딧 : 제품 공개 및 최적화 구축  
재료 성분-옵션 1 : 재료 성분보고

MR 크레딧 : 제품 공개 및 최적화 구축  
환경 제품 선언-옵션 1 : 환경 제품 선언 (EPD)

EQ 크레딧 : 저 발광 재료  
옵션 1 : 제품 범주 계산

Installation Guidelines

Health Product Declaration (HPD) | 100 Ppm Disclosure

3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017













FloorScore Certified

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information.  
Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

Available Colorways

					
Beige 65114 LRV 51.2 V1 - Uniform Appearance	Stone 65115 LRV 26.7 V1 - Uniform Appearance	Yellow 65201 LRV 42.6 V1 - Uniform Appearance	Green 65326 LRV 23.2 V1 - Uniform Appearance	Blue 65429 LRV 9.8 V1 - Uniform Appearance	Cyan 65436 LRV 18.7 V1 - Uniform Appearance
					
Bone 65515 LRV 54.8 V1 - Uniform Appearance	Grey 65530 LRV 26.2 V1 - Uniform Appearance	Charcoal 65595 LRV 12.1 V1 - Uniform Appearance	Orange 65675 LRV 19.9 V1 - Uniform Appearance	Taupe 65761 LRV 13.4 V1 - Uniform Appearance	Red 65855 LRV 11.1 V1 - Uniform Appearance

Color and Visual Variation Index

Shade and texture variation is inherent in all resilient products and can vary significantly from piece to piece. Samples should be used to assess color.

